

1. Identification of the substance/preparation and company/undertaking

Product name	Syntilo 2 NF
SDS no.	465514
Use of the substance/mixture	Metalworking fluid - soluble. Synthetic. For specific application advice see appropriate Technical Data Sheet or consult our company representative.
Supplier	Castrol India Ltd Technopolis Knowledge Park Office PO Box 19411 Mahakali Caves Rd Chakala, Andheri (E) Mumbai 400093 Telephone: +91 (022) 66984111/66984112
EMERGENCY TELEPHONE NUMBER	Toll free: 000800 100 7479 (for use in India only - 24 hours) Carechem Singapore: +65 3158 1198 (24 hours)
E-mail address	MSDSadvice@bp.com

2. Hazards identification

This preparation is not classified as dangerous according to Directive 1999/45/EC as amended and adapted.

Additional hazards Defatting to the skin.

See sections 11 and 12 for more detailed information on health effects and symptoms and environmental hazards.

3. Composition/information on ingredients

Corrosion inhibitors and additives in aqueous solution.

This product does not contain any hazardous ingredients at or above regulated thresholds.

4. First-aid measures

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.
Skin contact	Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if irritation develops.
Inhalation	If inhaled, remove to fresh air. Get medical attention if symptoms appear. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur. Wash out mouth with water if person is conscious.
Notes to physician	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. Treatment should in general be symptomatic and directed to relieving any effects.

5. Fire-fighting measures

Extinguishing media	
Suitable	In case of fire, use water fog, alcohol resistant foam, dry chemical or carbon dioxide extinguisher or spray.
Not suitable	Do not use water jet.
Hazardous decomposition products	Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides
Unusual fire/explosion hazards	In a fire or if heated, a pressure increase will occur and the container may burst.
Special fire-fighting procedures	Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.
Protection of fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6 . Accidental release measures

Personal precautions - For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Floors may be slippery; use care to avoid falling. Put on appropriate personal protective equipment.

Personal precautions - For emergency responders

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Large spill

Immediately contact emergency personnel. Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

Small spill

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Reference to other sections

See Section 1 for emergency contact information.
See Section 5 for firefighting measures.
See Section 8 for information on appropriate personal protective equipment.
See Section 12 for environmental precautions.
See Section 13 for additional waste treatment information.

7 . Handling and storage

Handling - Protective measures

Put on appropriate personal protective equipment. Wash thoroughly after handling. Avoid breathing vapour or mist. During metal working, solid particles from workpieces or tools will contaminate the fluid and may cause abrasions of the skin. Where such abrasions result in a penetration of the skin, first aid treatment should be applied as soon as reasonably possible. The presence of certain metals in the workpiece or tool, such as chromium, cobalt and nickel, can contaminate the metalworking fluid and as a result may induce allergic skin reactions. Avoid prolonged or repeated contact with skin. Evaporation of water from soluble cutting fluids during use may lead to an increase in concentration which may result in the development of skin conditions due to irritation and defatting. It is important to monitor fluid strength on a regular basis with a refractometer and maintain it at the recommended concentration. Lubricants from other sources and other contaminants should be minimised. Swarf and other debris should be removed. To maintain optimum performance and minimise bacterial spoilage, machine tool coolant systems should be cleaned on a regular basis.

Handling - Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Storage

Store and use only in equipment/containers designed for use with this product. Keep away from heat and direct sunlight. Protect from freezing. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10).

Not suitable

Prolonged exposure to elevated temperature

8 . Exposure controls/personal protection

Occupational exposure limits

This product does not have any assigned OELs.

Exposure controls

Occupational exposure controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapours below their respective occupational exposure limits.

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal protective equipment

Respiratory protection

Respiratory protective equipment is not normally required where there is adequate natural or local exhaust ventilation to control exposure.

In case of insufficient ventilation, wear suitable respiratory equipment.

The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Hand protection

Wear protective gloves if prolonged or repeated contact is likely.
Recommended: Nitrile gloves.

The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Eye protection

Safety glasses with side shields.

Skin and body

Use of protective clothing is good industrial practice.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Personal protective equipment (Pictograms)

9 . Physical and chemical properties

General information**Appearance****Physical state**

Liquid.

Colour

Yellow.

Odour

Mild

Important health, safety and environmental information**Flash point**

Open cup: >100°C (>212°F) [Estimated. Water content interferes with flash point determination.]

pH

8.2 [Conc. (% w/w): 5%]

Density

>1000 kg/m³ (>1 g/cm³) at 15°C

Solubility

Soluble in water.

10 . Stability and reactivity

Stability

The product is stable.

Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous polymerisation will not occur.
Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid

No specific data.

Materials to avoid

Reactive or incompatible with the following materials: oxidising materials.
Slightly reactive or incompatible with the following materials: acids.

Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11 . Toxicological information

Acute toxicity**Effects and symptoms****Eyes**

Not classified as an eye irritant. Likely to cause transient stinging or redness if accidental eye contact occurs.

Skin

Defatting to the skin. May cause skin dryness and irritation.

Inhalation

Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure. May cause irritation to eyes, nose and throat due to exposure to vapour, mists or fumes.

Ingestion

Ingestion of large quantities may cause nausea and diarrhoea.

Chronic effects

Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

12 . Ecological information

Persistence/degradability

Expected to be biodegradable.

Mobility

Liquid. Soluble in water.

Environmental hazards

Not classified as dangerous.

13 . Disposal considerations

Disposal considerations / Waste information

The generation of waste should be avoided or minimised wherever possible. Waste product residues should not be disposed of via the sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Special precautions

Diluted Fluid The spent diluted fluid comprises a relatively stable emulsion. Dispose of via an authorised person/ licensed waste disposal contractor or by other suitable waste treatment techniques (e.g. emulsion splitting, coagulation and filtration) approved by the local authority. Spent fluid should never be disposed of down the drain. The aqueous phase should not be discharged into sewage systems unless provided for by local regulations; the non-aqueous phase should be disposed of as undiluted fluid. Note that separated aqueous solutions or effluents may contain metal salts as well as traces of oil and must be checked for conformity in these respects against consents given by the authorities before disposal. Further treatment may be required.

Unused product

Waste code	Waste designation
13 02 05*	mineral-based non-chlorinated engine, gear and lubricating oils

However, deviation from the intended use and/or the presence of any potential contaminants may require an alternative waste disposal code to be assigned by the end user.

Packaging

Waste code	European waste catalogue (EWC)
15 01 10*	packaging containing residues of or contaminated by dangerous substances

14 . Transport information

Not classified as hazardous for transport (ADR/RID, ADN, IMDG, ICAO/IATA)

15 . Regulatory information

Label requirements

Risk phrases

This product is not classified according to EU legislation.

Additional warning phrases

Contains 2,2'-[[[(5-methyl-1H-benzotriazol-1-yl)methyl]imino]bisethanol, 2,2'-[[[(4-methyl-1H-benzotriazol-1-yl)methyl]imino]bisethanol. May produce an allergic reaction.

Other regulations

REACH Status

For the REACH status of this product please consult your company contact, as identified in Section 1.

United States inventory (TSCA 8b)

At least one component is not listed.

Australia inventory (AICS)

Not determined.

Canada inventory

At least one component is not listed.

China inventory (IECSC)

All components are listed or exempted.

Japan inventory (ENCS)

Not determined.

Korea inventory (KECI)

All components are listed or exempted.

Philippines inventory (PICCS)

Not determined.

16 . Other information

History

Date of issue/ Date of revision

25/06/2013.

Date of previous issue

13/06/2013.

Prepared by

Product Stewardship

Notice to reader

Indicates information that has changed from previously issued version.

Product name Syntilo 2 NF

Product code 465514-IN02

Page: 4/5

Date of issue 25 June 2013

Format India

Language ENGLISH

(India)

(ENGLISH)

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.