

Page: 1

Revised edition no: 1 Date: 6/7/2012

Supersedes: 1/2/2012

# **Gulf ATF Type F**

PRODUCT CODE 2508

## SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier:

 Product name : Gulf ATF Type F

1.2. Relevant identified uses of the substance or mixture and uses advised against:

 Relevant identified uses : Automatic Transmission Fluid.

· Uses advised against : This oil should not be used for any other purpose than the intended use as an

automatic transmission fluid without expert advice.

1.3. Details of the supplier of the Safety Data Sheet:

: Gulf Oil Nederland B.V. Supplier

Ambachtsweg 31

1785 AJ - Den Helder - Nederland

Tel: +31 (0)223 634567

E-mail: technicalsupport@gulf.nl

Internet: www.gulf.nl

1.4. Emergency telephone number:

 Phone number(s) : +31 (0)223 634567

# **SECTION 2. Hazards identification**

## 2.1. Classification of the substance or mixture:

1999/45/EC

Classification according to Directive: This product does not meet the classification requirements of the current European

legislation.

2.2. Label elements:

: Do not empty into drains; dispose of this material and its container in a safe way. · Safety advices

2.3. Other hazards : Flammable liquid. Injection under the skin can occur when using high pressure

equipment. Overexposure to oil mist may cause respiratory irritations. Spills of this

product present a serious slipping hazard.

2.4 Other information : This mixture does not meet the criteria for PBT or vPvB according to Regulation (

EC) No 1907/2006, Annex XIII.

## SECTION 3. Composition/information on ingredients

#### 3.2. Mixtures:

: Mixture of highly refined mineral oils (PCA-content < 3% - IP 346) and additives. Description of the mixture Product is not considered to be hazardous but contains hazardous components.

Composition of the mixture:

Substance name CAS No EC No Ref REACH Classification Contents Annex No 64742-46-7 265-148-2 Distillates (petroleum), 2.5 - 10 % 649-221-00-X

hydrotreated middle - Gasoil

Other information : For full text of all R-phrases: see SECTION 16.

### **SECTION 4. First aid measures**

General advice : In case of accident or if you feel unwell, seek medical advice immediately

(show the label when possible).

## Gulf Oil Nederland B.V.

Ambachtsweg 31 1785 AJ - Den Helder - Nederland

Tel: +31 (0)223 634567

E-mail: technicalsupport@gulf.nl



Page : 2

Revised edition no : 1

Date : 6 / 7 / 2012

Supersedes: 1/2/2012

**Gulf ATF Type F** 

PRODUCT CODE 2508

## **SECTION 4. First aid measures (continued)**

#### 4.1. Description of first aid measures:

• After inhalation : Assure fresh air breathing. If you feel unwell, seek medical advice.

After contact with skin
 Remove contaminated clothing and shoes. Wash skin thoroughly with mild soap

and water. Never use kerosine or gasoline for cleaning the skin.

• After contact with the eyes : Rinse immediately with plenty of water. Seek medical attention if irritation develops.

• After ingestion : Do not induce vomiting. Seek medical attention immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed:

• After exposure : No acute or delayed symptoms or effects are anticipated if first aid treatment is

applied and is effective.

#### 4.3. Indication of any immediate medical attention and special treatment needed:

• After exposure : If injected under the skin when using high pressure equipment, send casualty

immediately to a hospital, even when there are few or no symptoms.

# **SECTION 5. Firefighting measures**

### 5.1. Extinguishing media:

• Suitable extinguishing media : Water fog. Carbon dioxide. Foam. Dry chemical product.

• Unsuitable extinguishing media : Do not use a heavy water stream.

# 5.2. Special hazards arising from the substance or mixture:

• In the event of a fire : Under fire conditions, hazardous fumes will be present.

5.3. Advice for firefighters:

Protective actions : Avoid fire-fighting water to enter environment.

Special protective equipment for

fire-fighters

: Wear self-contained breathing apparatus, rubber boots and thick rubber gloves. Do not enter fire area without proper protective equipment, including respiratory

protection.

• Surrounding fires : Use water spray or fog for cooling exposed containers.

#### **SECTION 6. Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures:

• For non-emergency personnel : Evacuate unnecessary personnel.

• For emergency responders : Equip cleanup crew with proper protection. Wear suitable protective clothing, gloves and eye or face protection. Eliminate every possible source of ignition.

6.2. Environmental precautions:

• In case of accidental spills : Avoid release to the environment. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Notify authorities if liquid enters

prevent migration and entry into sewers or streams. Notify authorities if liquid enters sewers or public waters.

and and material for containment and cleaning up.

# 6.3. Methods and material for containment and cleaning up:

• Appropriate containment techniques : Clean up any spills as soon as possible, using an absorbent material to collect it.

• Appropriate clean-up procedures : Clean up even minor leaks or spills and spread granular absorbent promptly.

Collect spills and put it into appropriated container.

**6.4. Reference to other sections** : See also sections 8 & 13.

#### Gulf Oil Nederland B.V.

Ambachtsweg 31 1785 AJ - Den Helder - Nederland

Tel: +31 (0)223 634567

E-mail: technicalsupport@gulf.nl



Page : 3

Revised edition no : 1

Date : 6 / 7 / 2012

Supersedes: 1 / 2 / 2012

# **Gulf ATF Type F**

PRODUCT CODE 2508

## SECTION 7. Handling and storage

## 7.1. Precautions for safe handling:

Measures to prevent fire, aerosol

and dust generation

 Measures to protect the environment

 Advice on general occupational hygiene : Keep away from sources of ignition. No naked lights. No smoking. Proper grounding procedures to avoid static electricity should be followed.

: Contain any spills with dikes or absorbents to prevent migration and entry into

sewers or streams.

: When using, do not eat, drink or smoke. Wash hands and other exposed areas

with soap and water before leaving work.

#### 7.2. Conditions for safe storage, including any incompatibilities:

• Technical protective measures : Local exhaust and general ventilation must be adequate to meet exposure

standards.

• Conditions of storage : Store this product in a dry location where it can be protected from the elements. Do

not store near oxidizing agents or acidic material. Keep at temperature not

exceeding 45 ℃.

• Specific designs for storage rooms

or vessels

: Store in tightly closed, properly ventilated containers away from heat, sparks, open

flame, strong oxidizers, radiations, and other initiators.

7.3. Specific end use(s):

• Recommendations : See Product Data Sheet for detailed information.

# SECTION 8. Exposure controls/personal protection

## 8.1. Control parameters:

• Occupational exposure limit values: : United Kingdom: Occupational Exposure Standard (OES) of 5 mg/m³,

8-hour time-weighted average reference period for oil mist.

The American Conference of Governmental Industrial Hygienists (ACGIH) has assigned mineral oil mist a threshold limit value (TLV) of 5 mg/m³ as a Time Weighted Average (TWA) for a normal 8-hour workday and a 40-hour workweek and a short-term exposure limit (STEL) of 10 mg/m³ for periods not to exceed 15 minutes. Exposures at the STEL concentration should not be repeated more than four times a day and should be separated by intervals of at least 60 minutes.

[ACGIH 1994, p. 28]

• Biological limit values : No data available.

8.2. Exposure controls:

#### 8.2.1 Appropriate engineering controls:

Technical measures to prevent

: Use adequate ventilation to keep oil mist below applicable standard.

exposure

## 8.2.2 Individual protection measures, such as personal protective equipment:

• Eye / face protection : Chemical goggles or safety glasses.(EN 166)

Skin protection
 Wear suitable protective clothing. (EN 465, EN 466 or EN 467).
 Hand protection
 Wear suitable gloves resistant to chemical penetration. (EN 374)

• Respiratory protection : The use of Filtertype A (EN 141) is recommended If exceeding the Occupational

Exposure Limit.

• Other : Do not wear leather soled shoes.

#### 8.2.3 Environmental exposure controls:

• Measures to prevent exposure : Avoid release to the environment.

See Heading 6.

## Gulf Oil Nederland B.V.

Ambachtsweg 31 1785 AJ - Den Helder - Nederland

Tel: +31 (0)223 634567

E-mail: technicalsupport@gulf.nl



Page:4

Revised edition no : 1

Date : 6 / 7 / 2012

Supersedes: 1 / 2 / 2012

**Gulf ATF Type F** 

PRODUCT CODE 2508

### SECTION 9. Physical and chemical properties

## 9.1. Information on basic physical and chemical properties:

Appearance:

- Physical state- Colour: Oily liquid.: Red.

• Odour : Light odour of petroleum.

Pour point (ASTM-D97)
 Flash point (ASTM-D92)
 Density @ 15 °C (ASTM-D4052)
 Solubility(ies)
 Viscosity @ 40 °C (ASTM-D445)
 - 42 °C
 195 °C
 865 kg/m³
 Insoluble.
 34.9 mm²/s ( cSt)

**9.2. Other information** : See Product Data Sheet for detailed information.

## SECTION 10. Stability and reactivity

**10.1 Reactivity** : No data available.

10.2 Chemical stability : Stable under normal conditions.10.3 Possibility of hazardous : None under normal conditions.

reactions

: Extremely high or low temperatures.

**10.5** Incompatible materials : Strong oxidizing agents.

10.6 Hazardous decomposition

10.4 Conditions to avoid

products

: None under normal conditions.

## **SECTION 11. Toxicological information**

#### 11.1. Information on toxicological effects:

Acute toxicity
 No specific toxicity data on this product available.

Irritation : Not expected to be irritant. Prolonged or repeated skin contact with the material will

remove natural oils and could lead to a dermatitis.

• Corrosivity : No adverse health effects were noted.

• Sensitisation : No sensitization effects known.

Repeated dose toxicity : Not applicable.

• Carcinogenicity : This product contains mineral oils which are considered to be severely refined and

not considered to be carcinogenic under IARC. All of the oils in this product have been demonstrated to contain less than 3% extractables by the IP 346 test.

Mutagenicity : Not expected to be mutagenetic.

• Toxicity for reproduction : Not expected to be toxic.

# 11.2. Information on likely routes of exposure:

• After ingestion : Ingestion may cause nausea, vomiting and diarrhoea.

After inhalation : Not expected to present a significant inhalation hazard under anticipated conditions

of normal use.

• After skincontact : Prolonged or repeated skin contact with the material will remove natural oils and

could lead to a dermatitis.

#### Gulf Oil Nederland B.V.

Ambachtsweg 31 1785 AJ - Den Helder - Nederland

Tel: +31 (0)223 634567

E-mail: technicalsupport@gulf.nl



Page : 5

Revised edition no : 1

Date : 6 / 7 / 2012

Supersedes: 1 / 2 / 2012

**Gulf ATF Type F** 

PRODUCT CODE 2508

# **SECTION 11. Toxicological information (continued)**

After eyecontact : Slight eye irritant upon direct contact.

## 11.3. Symptoms related to the physical, chemical and toxicological characteristics:

• General : No adverse symptoms/effects were noted.

#### 11.4. Delayed and immediate effects as well as chronic effects from short and long-term exposure:

• General : No acute or delayed symptoms or effects are anticipated if first aid treatment is

applied and is effective.

**11.5.** Other toxicological information: No data available.

## **SECTION 12. Ecological information**

#### 12.1. Toxicity:

## Acute (short-term) toxicity:

• Chronic (long-term) toxicity: : No specific toxicity data on this product available.

**12.2. Persistence and degradability** : Not readily biodegradable.

12.3. Bioaccumulative potential : Not determined.12.4. Mobility in soil : No data available.

12.5. Results of PBT and vPvB

assessment

: This mixture does not contain any substances that are assessed to be a PBT or a

vPvB.

**12.6 Other adverse effects** : Spills may contaminate water supplies / pollute public waters.

# **SECTION 13. Disposal considerations**

## 13.1. Waste treatment methods:

• Waste disposal : Dispose of this material and its container to hazardous or special waste collection

point, in accordance with local, regional, national and/or international regulation.

Recover waste liquids for recycling/re-use. See Directive 2001/118/EC.

• Waste Code European Waste List : 13 02 05 - mineral-based non-chlorinated engine, gear and lubricating oils.

15 01 10 - packaging containing residues of or contaminated by dangerous

substances.

#### **SECTION 14. Transport information**

Not regulated.

## **SECTION 15. Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture:

#### 15.1.1 National regulations:

• Germany : Water Hazard Class: 1 - slightly hazardous to water

• Netherlands : Water pollution effect indication {11}: Slightly harmful to aquatic organisms.

Abatement effort: B

#### 15.1.2 International Regulations:

#### Gulf Oil Nederland B.V.

Ambachtsweg 31 1785 AJ - Den Helder - Nederland

Tel: +31 (0)223 634567

E-mail: technicalsupport@gulf.nl



Page : 6

Revised edition no : 1

Date : 6 / 7 / 2012

Supersedes: 1 / 2 / 2012

**Gulf ATF Type F** 

PRODUCT CODE 2508

# **SECTION 15. Regulatory information (continued)**

• Europe : All components listed in the European Inventory of Existing Commercial Chemical

Substances (EINECS)

**15.2.** Chemical safety assessment : No chemical safety assessment has been carried out for this mixture.

#### **SECTION 16. Other information**

• Indication of changes : Revision according to Regulation (EU) No 453/2010 amending Regulation (EC) No

1907/2006.

• **Abbreviations and acronyms** : ACGIH = American Conference of Industrial Hygienists

CLP = Classification and Labelling of Substances and Preparations

DOT = Department of Transport

EC = European Commission. EN = European Norm IARC= International Agency for Research on Cancer

IP = Institute of Petroleum

ISO = International Organization for Standardization NLGI = National Lubricating Grease Institute PBT = Persistent Bioaccumulative and Toxic

PCA = Polycyclic Aromatics

SAE = Society of Automotive Engineers

TLV = Threshold Limit Value. TWA = Time Weighted Average

vPvB = very Persistent and very Bioaccumulative

VG = Viscosity Grade

Key literature references and

sources for data

: Concawe Report 01/53, Concawe Report 01/54, Concawe Report 05/87. Regulations (EC) No 1907/2006, 1272/2008 & 453/2010 of the European

Parliament and of the Council.

· List of relevant R-phrases

Training advice

• Further information

: R65: Harmful: may cause lung damage if swallowed.: See information supplied by the manufacturer.

: Specifications and technical informations on the product may be obtained by your

dealer.

The contents and format of this SDS are in accordance with COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.

End of document

Gulf Oil Nederland B.V.

Ambachtsweg 31 1785 AJ - Den Helder - Nederland

Tel: +31 (0)223 634567

E-mail: technicalsupport@gulf.nl