

Page: 1

Revised edition no: 1 Date: 20 / 6 / 2012

Supersedes: 6 / 12 / 2011

Gulf Formula RNX 5W-30

PRODUCT CODE 1208

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier:

 Product name : Gulf Formula RNX 5W-30

: SAE 5W-30 Viscosity Grade

1.2. Relevant identified uses of the substance or mixture and uses advised against:

· Relevant identified uses : Engine oil (lubricant)

: This oil should not be used for any other purpose than the intended use as an Uses advised against

engine oil without expert advice.

1.3. Details of the supplier of the Safety Data Sheet:

: Gulf Oil Nederland B.V. Supplier

Ambachtsweg 31

1785 AJ - Den Helder - Nederland

Tel: +31 (0)223 634567

E-mail: technicalsupport@gulf.nl

Internet: www.gulf.nl

1.4. Emergency telephone number:

: +31 (0)223 634567 Phone number(s)

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture:

1999/45/EC

• Classification according to Directive: This product does not meet the classification requirements of the current European

legislation.

2.2. Label elements:

· Safety advices : Contains triazole derivative. May produce an allergic reaction. Do not empty into

drains; dispose of this material and its container in a safe way.

: Flammable liquid. Prolonged or repeated skin contact with the material will remove 2.3. Other hazards

natural oils and could lead to a dermatitis. Spills of this product present a serious slipping hazard. Overexposure to oil mist may cause respiratory irritations. This mixture does not meet the criteria for PBT or vPvB according to Regulation (EC) No

1907/2006, Annex XIII.

SECTION 3. Composition/information on ingredients

3.2. Mixtures:

: Mixture of synthetic base oils (PCA-content < 3% - IP 346) and additives. · Description of the mixture

Product is not considered to be hazardous but contains hazardous components.

· Composition of the mixture:

-							
Substance name		Contents	CAS No	EC No	Annex No	Ref REACH	Classification
Distillates (petroleum), hydrotreated heavy paraffinic	:	70 - 75 %	64742-54-7	265-157-1	649-467-00-8		Not classified. (DSD/DPD)
Zinc alkyl dithiophosphate	:	1 - 2 %	68649-42-3	272-028-3			Xi; R38-41 N; R51-53
triazole derivative	:	0,1 -1%	91273-04-0	401-280-0	613-072-00-9		C; R34 R43 N; R51-53

Other information : For full text of all R-phrases: see SECTION 16.

Gulf Oil Nederland B.V.

Ambachtsweg 31 1785 AJ - Den Helder - Nederland

Tel: +31 (0)223 634567

E-mail: technicalsupport@gulf.nl



Page : 2

Revised edition no : 1

Date : 20 / 6 / 2012

Supersedes: 6 / 12 / 2011

Gulf Formula RNX 5W-30

PRODUCT CODE 1208

SECTION 4. First aid measures

General advice : In case of accident or if you feel unwell, seek medical advice immediately

(show the label when possible).

4.1. Description of first aid measures:

After inhalation
 : Assure fresh air breathing. If you feel unwell, seek medical advice.

• After contact with skin : Remove contaminated clothing and shoes. Wash skin thoroughly with mild soap

and water. Never use kerosine or gasoline for cleaning the skin.

• After contact with the eyes : Rinse immediately with plenty of water. Seek medical attention if irritation develops.

• After ingestion : Do not induce vomiting. Seek medical attention immediately.

4.2. Most important symptoms and effects, both acute and delayed:

• After exposure : No acute or delayed symptoms or effects are anticipated if first aid treatment is

applied and is effective.

4.3. Indication of any immediate medical attention and special treatment needed:

After exposure : If injected under the skin when using high pressure equipment, send casualty

immediately to a hospital, even when there are few or no symptoms.

SECTION 5. Firefighting measures

5.1. Extinguishing media:

• Suitable extinguishing media : Water fog. Carbon dioxide. Foam. Dry chemical product.

• Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture:

• In the event of a fire : Under fire conditions, hazardous fumes will be present.

5.3. Advice for firefighters:

Protective actions
 Avoid fire-fighting water to enter environment.

Special protective equipment for

fire-fighters

: Do not enter fire area without proper protective equipment, including respiratory protection. Wear self-contained breathing apparatus, rubber boots and thick rubber

gloves.

Surrounding fires
 Use water spray or fog for cooling exposed containers.

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures:

• For non-emergency personnel : Evacuate unnecessary personnel.

• For emergency responders : Equip cleanup crew with proper protection. Wear suitable protective clothing, gloves and eye or face protection. Eliminate every possible source of ignition.

6.2. Environmental precautions:

• In case of accidental spills : Avoid release to the environment. Contain any spills with dikes or absorbents to

prevent migration and entry into sewers or streams. Notify authorities if liquid enters

sewers or public waters.

6.3. Methods and material for containment and cleaning up:

• Appropriate containment techniques : Contain any spills with dikes or absorbents to prevent migration and entry into

sewers or streams.

Gulf Oil Nederland B.V.

Ambachtsweg 31 1785 AJ - Den Helder - Nederland

Tel: +31 (0)223 634567

E-mail: technicalsupport@gulf.nl



Page: 3

Revised edition no: 1 Date: 20 / 6 / 2012

Supersedes: 6 / 12 / 2011

Gulf Formula RNX 5W-30

PRODUCT CODE 1208

SECTION 6. Accidental release measures (continued)

Appropriate clean-up procedures

: Clean up even minor leaks or spills and spread granular absorbent promptly.

Collect spills and put it into appropriated container.

6.4. Reference to other sections

: See also sections 8 & 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling:

 Measures to prevent fire, aerosol and dust generation

Measures to protect the

environment

: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

 Advice on general occupational hygiene

: When using, do not eat, drink or smoke. Wash hands and other exposed areas

with soap and water before leaving work.

7.2. Conditions for safe storage, including any incompatibilities:

Technical protective measures

: Local exhaust and general ventilation must be adequate to meet exposure

: Keep away from sources of ignition. No naked lights. No smoking. Proper

grounding procedures to avoid static electricity should be followed.

standards.

Conditions of storage

: Store this product in a dry location where it can be protected from the elements. Do

not store near oxidizing agents or acidic material. Keep at temperature not

exceeding 50 ℃.

or vessels

• Specific designs for storage rooms : Store in tightly closed, properly ventilated containers away from heat, sparks, open

flame, strong oxidizers, radiations, and other initiators.

7.3. Specific end use(s):

: See Product Data Sheet for detailed information. Recommendations

SECTION 8. Exposure controls/personal protection

8.1. Control parameters:

Occupational exposure limit values: : United Kingdom: Occupational Exposure Standard (OES) of 5 mg/m³,

8-hour time-weighted average reference period for oil mist.

The American Conference of Governmental Industrial Hygienists (ACGIH) has assigned mineral oil mist a threshold limit value (TLV) of 5 mg/m³ as a Time Weighted Average (TWA) for a normal 8-hour workday and a 40-hour workweek and a short-term exposure limit (STEL) of 10 mg/m3 for periods not to exceed 15 minutes. Exposures at the STEL concentration should not be repeated more than four times a day and should be separated by intervals of at least 60 minutes.

[ACGIH 1994, p. 28]

 Biological limit values No data available.

8.2. Exposure controls:

8.2.1 Appropriate engineering controls:

 Technical measures to prevent exposure

: Use adequate ventilation to keep oil mist below applicable standard.

8.2.2 Individual protection measures, such as personal protective equipment:

: Chemical goggles or safety glasses.(EN 166) Eye / face protection

: Wear suitable protective clothing. (EN 465, EN 466 or EN 467). Skin protection

Gulf Oil Nederland B.V.

Ambachtsweg 31 1785 AJ - Den Helder - Nederland

Tel: +31 (0)223 634567

E-mail: technicalsupport@gulf.nl



Page : 4

Revised edition no : 1

Date : 20 / 6 / 2012

Supersedes: 6 / 12 / 2011

Gulf Formula RNX 5W-30

PRODUCT CODE 1208

SECTION 8. Exposure controls/personal protection (continued)

• Hand protection : Wear suitable gloves resistant to chemical penetration. (EN 374)

• Respiratory protection : The use of Filtertype A (EN 141) is recommended If exceeding the Occupational

Exposure Limit.

• Other : Do not wear leather soled shoes.

8.2.3 Environmental exposure controls:

• Measures to prevent exposure : Avoid release to the environment. See Heading 6.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties:

- Physical state- Colour: Oily liquid.: Slightly yellow.

• Odour : Light odour of petroleum.

• Pour point (ASTM-D97) : -33 °C • Flash point (ASTM-D92) : 210 °C • Density @ 15 °C (ASTM-D4052) : 851 kg/m³

• Solubility(ies) : Material insoluble in water.

• Viscosity @ 40 °C (ASTM-D445) : 68.1 cSt

9.2. Other information:

• General information : See Product Data Sheet for detailed information.

SECTION 10. Stability and reactivity

10.1 Reactivity : No data available.

10.2 Chemical stability : Stable under normal conditions.10.3 Possibility of hazardous : None under normal conditions.

reactions

10.4 Conditions to avoid : Extremely high or low temperatures.

10.5 Incompatible materials : Strong oxidizing agents.10.6 Hazardous decomposition : None under normal conditions.

products

ucts

SECTION 11. Toxicological information

11.1. Information on toxicological effects:

Acute toxicity
 No specific toxicity data on this product available.

• Irritation : Not expected to be irritant.

Corrosivity : No adverse health effects were noted.Sensitisation : No sensitization effects known.

• Repeated dose toxicity : Not applicable.

Carcinogenicity : Not expected to be carcinogenetic.
 Mutagenicity : Not expected to be mutagenetic.

Gulf Oil Nederland B.V.

Ambachtsweg 31 1785 AJ - Den Helder - Nederland

Tel: +31 (0)223 634567

E-mail: technicalsupport@gulf.nl



Page : 5

Revised edition no : 1
Date : 20 / 6 / 2012

Supersedes: 6 / 12 / 2011

Gulf Formula RNX 5W-30

PRODUCT CODE 1208

SECTION 11. Toxicological information (continued)

• Toxicity for reproduction : Not expected to be toxic.

11.2. Information on likely routes of exposure:

After ingestion : Ingestion may cause nausea, vomiting and diarrhoea.

After inhalation
 Not expected to present a significant inhalation hazard under anticipated conditions

of normal use.

After skincontact
 Repeated or prolonged skin contact may cause irritation.

• After eyecontact : Slight eye irritant upon direct contact.

11.3. Symptoms related to the physical, chemical and toxicological characteristics:

• General : No adverse symptoms/effects were noted.

11.4. Delayed and immediate effects as well as chronic effects from short and long-term exposure:

• General : No acute or delayed symptoms or effects are anticipated if first aid treatment is

applied and is effective.

11.5. Other toxicological information : During use in engines, contamination of oil with low levels of cancer-causing

combustion products occurs. Used motor oils have been shown to cause skin cancer in mice following repeated application and continuous exposure. Brief or intermittent skin contact with used motor oil is not expected to have serious effects in humans if the oil is thoroughly removed by washing with soap and water. Avoid

prolonged contact with used motor oil.

SECTION 12. Ecological information

12.1. Toxicity:

Acute (short-term) toxicity:
 Chronic (long-term) toxicity:
 No specific toxicity data on this product available.
 No specific toxicity data on this product available.

12.2. Persistence and degradability : No data available.12.3. Bioaccumulative potential : No data available.

12.4. Mobility in soil : It is to be expected small mobility in soil. Some or a few components may get into

the soil and may cause pollution of ground water.

12.5. Results of PBT and vPvB

assessment

: This mixture does not contain any substances that are assessed to be a PBT or a

vPvB.

12.6 Other adverse effects : Spills may contaminate water supplies / pollute public waters.

SECTION 13. Disposal considerations

13.1. Waste treatment methods:

• Waste disposal : Dispose of this material and its container to hazardous or special waste collection

point, in accordance with local, regional, national and/or international regulation.

Recover waste liquids for recycling/re-use. See Directive 2001/118/EC.

• Waste Code European Waste List : 13 02 06 - synthetic engine, gear and lubricating oils.

15 01 10 - packaging containing residues of or contaminated by dangerous

substances.

Gulf Oil Nederland B.V.

Ambachtsweg 31 1785 AJ - Den Helder - Nederland

Tel: +31 (0)223 634567

E-mail: technicalsupport@gulf.nl



Page : 6

Revised edition no : 1

Date : 20 / 6 / 2012

Supersedes: 6 / 12 / 2011

Gulf Formula RNX 5W-30

PRODUCT CODE 1208

SECTION 14. Transport information

Not regulated.

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture:

15.1.1 National regulations:

• Germany : Water Hazard Class: 1 - slightly hazardous to water

• Netherlands : Water pollution effect indication {11}: Slightly harmful to aquatic organisms.

Abatement effort: B

15.1.2 International Regulations:

• Europe : All components listed in the European Inventory of Existing Commercial Chemical

Substances (EINECS)

• Australia : All components are in compliance with chemical notification requirements in

Australia. (AICS)

• Canada : All components are in compliance with the Canadian Environmental Protection Act

(CEPA) and are present on the Domestic Substances List.

• USA : All components of this material are on the US Toxic Substances Control Act

(TSCA) inventory or are exempt.

15.2. Chemical safety assessment : No chemical safety assessment has been carried out for this mixture.

SECTION 16. Other information

• Indication of changes : Revision according to Regulation (EU) No 453/2010 amending Regulation (EC) No

1907/2006.

• Abbreviations and acronyms : ACGIH = American Conference of Industrial Hygienists

CLP = Classification and Labelling of Substances and Preparations

DOT = Department of Transport

EC = European Commission. EN = European Norm IARC= International Agency for Research on Cancer

IP = Institute of Petroleum

ISO = International Organization for Standardization
NLGI = National Lubricating Grease Institute
PBT = Persistent Bioaccumulative and Toxic

PCA = Polycyclic Aromatics

SAE = Society of Automotive Engineers

TLV = Threshold Limit Value. TWA = Time Weighted Average

vPvB = very Persistent and very Bioaccumulative

VG = Viscosity Grade

Key literature references and

sources for data

: Concawe Report 01/53, Concawe Report 01/54, Concawe Report 05/87. Regulations (EC) No 1907/2006, 1272/2008 & 453/2010 of the European

Parliament and of the Council.

• List of relevant R-phrases : R34 : Causes burns.

R38: Irritating to skin.

R41: Risk of serious damage to eyes.

R43: May cause sensitization by skin contact.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Gulf Oil Nederland B.V.

Ambachtsweg 31 1785 AJ - Den Helder - Nederland

Tel: +31 (0)223 634567

E-mail: technicalsupport@gulf.nl



Page : 7

Revised edition no : 1

Date: 20 / 6 / 2012

Supersedes: 6 / 12 / 2011

Gulf Formula RNX 5W-30

PRODUCT CODE 1208

SECTION 16. Other information (continued)

Training advice

: See Product Data Sheet for detailed information.

The contents and format of this SDS are in accordance with COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.

End of document

Gulf Oil Nederland B.V.

Ambachtsweg 31 1785 AJ - Den Helder - Nederland

Tel: +31 (0)223 634567

E-mail: technicalsupport@gulf.nl