

Page : 1

Revised edition no : 1 Date : 10 / 7 / 2012

Supersedes : 29 / 2 / 2012

Gulf Pride 2T Plus

PRODUCT CODE 1910

| ECTION 1. Identification of th | e substance/r | nixture and | of the co | ompany/und | dertaking | |
|---|-------------------------------------|--|--------------------------------|------------------|---------------------------------------|---|
| 1.1. Product identifier: | | | | | | |
| Product name | : Gulf F | ride 2T Plus | | | | |
| 1.2. Relevant identified uses o | f the substance | or mixture a | and uses a | advised agai | <u>nst:</u> | |
| Relevant identified uses | : 2-stro | ke motorcycle | e engine oi | I | | |
| Uses advised against | | il should not engine oil wi | | | urpose than the int | ended use as a 2- |
| 1.3. Details of the supplier of t | he Safety Data | Sheet: | | | | |
| • Supplier | Amba 1785 Tel: + E-mai | 0il Nederland chtsweg 31 AJ - Den Hel 31 (0)223 634 I: technicalsu et: www.gulf.r | der - Ned 1567 pport@gul | | | |
| 1.4. Emergency telephone num | nber: | | | | | |
| Phone number(s) | : +31 (0 |))223 634567 | | | | |
| ECTION 2. Hazards identifica | tion | | | | | |
| 2.1. Classification of the subst | ance or mixtur | <u>e:</u> | | | | |
| Classification according to D 1999/45/EC | i rective :This p legisla | | not meet th | ne classificatio | on requirements o | f the current Europea |
| 2.2. Label elements: | | | | | | |
| Safety advices | : Do no | t empty into c | Irains ; dis | pose of this m | naterial and its cor | ntainer in a safe way. |
| 2.3. Other hazards | natura | al oils and cou | Id lead to | a dermatitis. | | e material will remove il mist may cause slipping hazard. |
| 2.4 Other information | | nixture does r No 1907/200 | | | PBT or vPvB acco | rding to Regulation |
| ECTION 3. Composition/infor | mation on ing | redients | | | | |
| Description of the mixture | additiv | /es. | | · | PCA-content < 3% but contains haza | 6 - IP346) and rdous components. |
| Composition of the mixture: | | | | | | |
| Substance name | Contents | CAS No | EC No | Annex No | Ref REACH | Classification |
| Lubricating oils (petroleum), C20- : 50, hydrotreated neutral oil-based | 40 - 50 % | 72623-87-1 | 276-738-4 | 649-483-00-5 | | Not classified. (DSD/DPD) |
| Lubricating oils(petroleum), C20- C50, hydrotreated neutral oil- based, high-viscosity. | 15 - 25 % | 72623-85-9 | 276-736-3 | 649-481-00-4 | | Not classified. (DSD/DPD) |
| Hydrocarbons, C11-C14, n- : alkanes, isoalkanes, cyclics, < 2% aromatics | 5 - 15 % | | 926-141-6 | | 01-2119456620-43 | Xn; R65 R66 |
| | - / | II text of all R | | | | |



Page : 2 Revised edition no : 1

Date : 10 / 7 / 2012

Supersedes : 29 / 2 / 2012

Gulf Pride 2T Plus

PRODUCT CODE 1910

| CTION 4. First aid measures | |
|---|---|
| General advice | : In case of accident or if you feel unwell, seek medical advice immediately (show the label when possible). |
| 4.1. Description of first aid measured | Jres: |
| After inhalation | : Assure fresh air breathing. If you feel unwell, seek medical advice. |
| After contact with skin | : Remove contaminated clothing and shoes. Wash skin thoroughly with mild soap and water. Never use kerosine or gasoline for cleaning the skin. |
| After contact with the eyes | : Rinse immediately with plenty of water. Seek medical attention if irritation develop |
| After ingestion | : Do not induce vomiting. Seek medical attention immediately. |
| 4.2. Most important symptoms an | nd effects, both acute and delayed: |
| After exposure | : No acute or delayed symptoms or effects are anticipated if first aid treatment is applied and is effective. |
| 4.3. Indication of any immediate r | medical attention and special treatment needed: |
| After exposure | : If injected under the skin when using high pressure equipment, send casualty immediately to a hospital, even when there are few or no symptoms. |

SECTION 5. Firefighting measures

| 5.1. Extinguishing media: | |
|--|--|
| Suitable extinguishing media | : Water fog. Carbon dioxide. Foam. Dry chemical product. |
| Unsuitable extinguishing media | : Do not use a heavy water stream. |
| 5.2. Special hazards arising from the | e substance or mixture: |
| In the event of a fire | : Under fire conditions, hazardous fumes will be present. |
| 5.3. Advice for firefighters: | |
| Protective actions | : Avoid fire-fighting water to enter environment. |
| Special protective equipment for fire-fighters | : Do not enter fire area without proper protective equipment, including respiratory protection. Wear self-contained breathing apparatus, rubber boots and thick rubber gloves. |
| Surrounding fires | : Use water spray or fog for cooling exposed containers. |

SECTION 6. Accidental release measures

| 6.1. Personal precautions, protectiv | e equipment and emergency procedures: |
|--|--|
| For non-emergency personnel | : Evacuate unnecessary personnel. |
| For emergency responders | : Equip cleanup crew with proper protection. Wear suitable protective clothing, gloves and eye or face protection. Eliminate every possible source of ignition. |
| 6.2. Environmental precautions: | |
| In case of accidental spills | : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Notify authorities if liquid enters sewers or public waters. |
| 6.3. Methods and material for conta | inment and cleaning up: |
| Appropriate containment technique | es : Clean up any spills as soon as possible, using an absorbent material to collect it. Take up large spills with pump or vacuum and finish with dry chemical absorbent. |
| Appropriate clean-up procedures | Clean up even minor leaks or spills and spread granular absorbent promptly. Collect spills and put it into appropriated container. |

Gulf Oil Nederland B.V.



Page : 3

Revised edition no : 1 Date : 10 / 7 / 2012

Supersedes : 29 / 2 / 2012

Gulf Pride 2T Plus

PRODUCT CODE 1910

SECTION 6. Accidental release measures (continued)

6.4. Reference to other sections : See also sections 8 & 13.

SECTION 7. Handling and storage

| 7.1. Precautions for safe handling: | |
|---|---|
| Measures to prevent fire, aerosol and dust generation | : Keep away from sources of ignition. No naked lights. No smoking. Proper grounding procedures to avoid static electricity should be followed. |
| Measures to protect the environment | : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. |
| Advice on general occupational hygiene | : When using, do not eat, drink or smoke. Wash hands and other exposed areas with soap and water before leaving work. |
| 7.2. Conditions for safe storage, inclu | uding any incompatibilities: |
| Technical protective measures | : Local exhaust and general ventilation must be adequate to meet exposure standards. |
| Conditions of storage | : Store this product in a dry location where it can be protected from the elements. Do not store near oxidizing agents or acidic material. Keep at temperature not exceeding 45 °C. |
| Specific designs for storage rooms or vessels | : Store in tightly closed, properly ventilated containers away from heat, sparks, open flame, strong oxidizers, radiations, and other initiators. |
| 7.3. Specific end use(s): | |
| Recommendations | : See Product Data Sheet for detailed information. |

SECTION 8. Exposure controls/personal protection

8.1. Control parameters:

| Occupational exposure limit values | :: : United Kingdom: Occupational Exposure Standard (OES) of 5 mg/m ³ , 8-hour time-weighted average reference period for oil mist. The American Conference of Governmental Industrial Hygienists (ACGIH) has assigned mineral oil mist a threshold limit value (TLV) of 5 mg/m ³ as a Time Weighted Average (TWA) for a normal 8-hour workday and a 40-hour workweek and a short-term exposure limit (STEL) of 10 mg/m ³ for periods not to exceed 15 minutes. Exposures at the STEL concentration should not be repeated more than four times a day and should be separated by intervals of at least 60 minutes. [ACGIH 1994, p. 28] |
|--|---|
| Biological limit values | : No data available. |
| 8.2. Exposure controls: | |
| 8.2.1 Appropriate engineering control | <u>bls:</u> |
| Technical measures to prevent exposure | : Use adequate ventilation to keep oil mist below applicable standard. |
| 8.2.2 Individual protection measures | s, such as personal protective equipment: |
| Eye / face protection | : Chemical goggles or safety glasses.(EN 166) |
| Skin protection | : Wear suitable protective clothing. (EN 465, EN 466 or EN 467). |
| Hand protection | : Wear suitable gloves resistant to chemical penetration. (EN 374) Use neoprene or rubber gloves. |



Page : 4 Revised edition no : 1

Date : 10 / 7 / 2012

Supersedes : 29 / 2 / 2012

Gulf Pride 2T Plus

PRODUCT CODE 1910

| Respiratory protection | : The use of Filtertype A (EN 141) is recommended If exceeding the Occupational Exposure Limit. | |
|--|---|--|
| • Other | : Do not wear leather soled shoes. | |
| 8.2.3 Environmental exposure cont | <u>rols:</u> | |
| Measures to prevent exposure | : Avoid release to the environment. See Heading 6. | |
| ECTION 9. Physical and chemical | properties | |
| 9.1. Information on basic physical a | and chemical properties: | |
| erri internation en saole priveleare | | |
| • Appearance: | | |
| | : Oily liquid. | |
| • Appearance: | | |
| Appearance: Physical state | : Oily liquid. | |
| Appearance: Physical state Colour | : Oily liquid. : Yellow-brown. | |
| Appearance: Physical state Colour Odour Pour point (ASTM-D97) | : Oily liquid. : Yellow-brown. : Light odour of petroleum. | |
| Appearance: Physical state Colour Odour Pour point (ASTM-D97) Flash point (ASTM-D92) | : Oily liquid. : Yellow-brown. : Light odour of petroleum. : <-18℃ | |
| Appearance: Physical state Colour Odour Pour point (ASTM-D97) | : Oily liquid. : Yellow-brown. : Light odour of petroleum. : <-18 ℃ : >100 ℃ | |
| Appearance: Physical state Colour Odour Pour point (ASTM-D97) Flash point (ASTM-D92) Density @ 15 ℃ (ASTM-D4052) | : Oily liquid. : Yellow-brown. : Light odour of petroleum. : <-18℃ : >100℃ : 873 kg/m³ | |

SECTION 10. Stability and reactivity

| 10.1 Reactivity 10.2 Chemical stability 10.3 Possibility of hazardous reactions | No data available.Stable under normal conditions.None under normal conditions. |
|--|--|
| 10.4 Conditions to avoid | : Extremely high or low temperatures. |
| 10.5 Incompatible materials | : Strong oxidizing agents. |
| 10.6 Hazardous decomposition products | : None under normal conditions. |

SECTION 11. Toxicological information

11.1. Information on toxicological effects:

| Acute toxicity | : No specific toxicity data on this product available. |
|--|--|
| Irritation | : Not expected to be irritant. |
| Corrosivity | : No adverse health effects were noted. |
| Sensitisation | : No sensitization effects known. |
| Repeated dose toxicity | : Not applicable. |
| Carcinogenicity | : This product contains mineral oils which are considered to be severely refined and not considered to be carcinogenic under IARC. All of the oils in this product have been demonstrated to contain less than 3% extractables by the IP 346 test. |
| Mutagenicity | : Not expected to be mutagenetic. |

Gulf Oil Nederland B.V.

Ambachtsweg 31 1785 AJ - Den Helder - Nederland Tel: +31 (0)223 634567 E-mail: technicalsupport@gulf.nl Internet: www.gulf.nl



Page : 5

Revised edition no : 1 Date : 10 / 7 / 2012

Gulf Pride 2T Plus

PRODUCT CODE 1910

Supersedes : 29 / 2 / 2012

SECTION 11. Toxicological information (continued)

| | : Not expected to be toxic. |
|--|---|
| 11.2. Information on likely routes of example. | (posure: |
| After ingestion | : Ingestion may cause nausea, vomiting and diarrhoea. |
| After inhalation | : Not expected to present a significant inhalation hazard under anticipated conditions of normal use. |
| After skincontact | : Repeated or prolonged skin contact may cause irritation. |
| After eyecontact | : Slight eye irritant upon direct contact. |
| 11.3. Symptoms related to the physica | II, chemical and toxicological characteristics: |
| General | : No adverse symptoms/effects were noted. |
| 11.4. Delayed and immediate effects a | s well as chronic effects from short and long-term exposure: |
| • General | : Prolonged or repeated skin contact with the material will remove natural oils and could lead to a dermatitis. |
| 11.5. Other toxicological information | : During use in engines, contamination of oil with low levels of cancer-causing combustion products occurs. Used motor oils have been shown to cause skin cancer in mice following repeated application and continuous exposure. Brief or intermittent skin contact with used motor oil is not expected to have serious effects in humans if the oil is thoroughly removed by washing with soap and water. Avoid prolonged contact with used motor oil. |

SECTION 12. Ecological information

| Acute (short-term) toxicity: | |
|--|---|
| Chronic (long-term) toxicity: | : No specific toxicity data on this product available. |
| 12.2. Persistence and degradability | : Not determined. |
| 12.3. Bioaccumulative potential | : Not determined. |
| 12.4. Mobility in soil | : It is to be expected small mobility in soil. Some or a few components may get into the soil and may cause pollution of ground water. |
| 12.5. Results of PBT and vPvB assessment | : This mixture does not contain any substances that are assessed to be a PBT or a vPvB. |
| 12.6 Other adverse effects | : Spills may contaminate water supplies / pollute public waters. |

SECTION 13. Disposal considerations

13.1. Waste treatment methods: • Waste disposal • Waste disposal : Dispose of this material and its container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. Recover waste liquids for recycling/re-use. See Directive 2001/118/EC. • Waste Code European Waste List : 13 02 05 - mineral-based non-chlorinated engine, gear and lubricating oils. 13 02 06 - synthetic engine, gear and lubricating oils. 15 01 10 - packaging containing residues of or contaminated by dangerous substances.



Page : 6 Revised edition no : 1

Date : 10 / 7 / 2012

Supersedes : 29 / 2 / 2012

Gulf Pride 2T Plus

PRODUCT CODE 1910

SECTION 14. Transport information

Not regulated.

SECTION 15. Regulatory information

| 15.1.1 National regulations: | |
|-----------------------------------|--|
| • Germany | : Water Hazard Class: 1 - slightly hazardous to water |
| Netherlands | : Water pollution effect indication {11}: Slightly harmful to aquatic organisms. Abatement effort: B |
| 15.1.2 International Regulations: | |
| • Europe | : All components listed in the European Inventory of Existing Commercial Chemical Substances (EINECS) |
| • Australia | : All components are in compliance with chemical notification requirements in Australia. (AICS) |
| • Canada | : All components are in compliance with the Canadian Environmental Protection Act (CEPA) and are present on the Domestic Substances List. |
| • USA | : All components of this material are on the US Toxic Substances Control Act (TSCA) inventory or are exempt. |
| 15.2. Chemical safety assessment | : No chemical safety assessment has been carried out for this mixture. |

SECTION 16. Other information

| Indication of changes | : Revision according to Regulation (EU) No 453/2010 amending Regulation (EC) No 1907/2006. |
|--|--|
| Abbreviations and acronyms | ACGIH = American Conference of Industrial Hygienists CLP = Classification and Labelling of Substances and Preparations DOT = Department of Transport EC = European Commission. EN = European Norm IARC= International Agency for Research on Cancer IP = Institute of Petroleum ISO = International Organization for Standardization NLGI = National Lubricating Grease Institute PBT = Persistent Bioaccumulative and Toxic PCA = Polycyclic Aromatics SAE = Society of Automotive Engineers TLV = Threshold Limit Value. TWA = Time Weighted Average vPvB = very Persistent and very Bioaccumulative VG = Viscosity Grade |
| Key literature references and sources for data | : Concawe Report 01/53, Concawe Report 01/54, Concawe Report 05/87. Regulations (EC) No 1907/2006, 1272/2008 & 453/2010 of the European Parliament and of the Council. |
| List of relevant R-phrases | : R65: Harmful: may cause lung damage if swallowed. R66 : Repeated exposure may cause skin dryness or cracking. |
| Training advice | : See Product Data Sheet for detailed information. |

The contents and format of this SDS are in accordance with COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).



Page : 7 Revised edition no : 1 Date : 10 / 7 / 2012

Supersedes : 29 / 2 / 2012

Gulf Pride 2T Plus

PRODUCT CODE 1910

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.

End of document