

MATERIAL SAFETY DATA SHEET

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY

Product name MAK RUSTROL 164

Product type Temporary Corrosion Preventive Fluid

Product Supplier Bharat Petroleum Corporation Limited,

4 & 6, Currimbhoy Road, Ballard Estate,

Mumbai – 400 001. Maharashtra.

India.

2. COMPOSITION/INFORMATION ON INGREDIENTS

Preparation description Blend of highly refined mineral oils, performance additives in

petroleum solvent

A. Highly refined Base Oils 89-91 % wt. **B.** Solvents 11-9 % wt.

The chemical identity of some or all the ingredients is confidential business information and is being withheld. In the event of a medical emergency, compositional information will be provided to medical

staff.

3. HAZARDS IDENTIFICATION

Human health hazards No specific hazards under normal use conditions. Prolonged or

repeated exposure may give rise to dermatitis and may cause central nervous system effects (including respiratory, motor difficulties & paralysis), digestive disturbances, liver & kidney

effects.

Safety hazards Classified as Class-B category under petroleum rules.

Environmental hazardsNot readily biodegradable. Expected to have a high potential

to bioaccumulate.

Other information Not classified as dangerous for supply or conveyance. Keep

containers closed when not in use.

4. FIRST AID MEASURES

Symptoms and effects Not expected to give rise to an acute hazard under normal

conditions of use

First Aid – Inhalation In the event of dizziness or nausea, remove casualty to fresh

air. If symptoms persist, obtain medical attention.

First Aid – Skin Remove contaminated clothing and wash affected skin

thoroughly with copious quantities of soap & water. Do not use solvent for cleaning. If persistent irritation occurs, obtain medical attention. If high pressure injection injuries occur, obtain medical attention immediately. Do not reuse contaminated clothing or shoes until thoroughly

decontaminated.

MAK RUSTROL 164 BHARAT PETROLEUM CORPORATION LTD.

PAGE 1 OF 5

Flush eye with copious quantities of water at least for 15 First Aid - Eye minutes. If persistent irritation occurs, obtain medical attention. **First Aid - Ingestion** DO NOT INDUCE VOMITING. If conscious give large quantities of water (if available give several quantities of milk) and get immediate medical attention. Advice to physicians Treat sympotomatically, aspiration into the lungs may result in chemical pneumonitis. Dermatitis may result from prolonged or repeated exposure. 5. FIRE FIGHTING MEASURES Specific hazards Combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates and gases, including carbon monoxide, oxides of sulphur, and unidentified organic and inorganic compounds. Dry Chemical Powder, Carbon dioxide, sand and earth may be **Extinguishing media** used. Unsuitable extinguishing media Use of Halon extinguishers should be avoided for environmental reasons. **Protective equipment** Trained personnel wearing breathing apparatus should deal with fires in confined spaces. 6. ACCIDENTAL RELEASE MEASURES **Personal precautions** Avoid contact with skin and eyes. **Personal protection** Wear impermeable gloves and boots. **Environmental precautions** Prevent from spreading or entering into drains, ditches or rivers by using sand, earth or other appropriate barriers. Inform local authorities if this cannot be prevented. Absorb liquid with sand or earth, Sweep up and remove to a Clean-up methods – small spillage suitable, clearly marked container for disposal in accordance with local regulations. Clean-up methods – large spillage Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Dispose of as for small spills. 7. HANDLING AND STORAGE Handling Carry out a health risk assessment to determine safe handling procedures and equipment that are necessary to avoid contact and that are appropriate to the job. Prevent spillages. Store in a cool, dry, well-ventilated place. Use properly Storage labeled and close-able containers. Avoid direct sunlight, heat sources, and strong oxidizing agents. 0 °C minimum to 27 °C maximum Storage temperature Use mild steel or high density polyethylene (HDPE) for **Recommended materials** containers or container linings. **Unsuitable materials** Avoid PVC for containers or container linings.

MAK RUSTROL 164

BHARAT PETROLEUM CORPORATION LTD.
PAGE 2 OF 5

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering control measures Exposure limit of 5 mg/m³ for oil mist applies (TWA, 8h-

workday) recommended based upon the ACGIH TLV (Analysis according to US NIOSH method 5026, NIOSH Manual of analytical methods, 3rd edition). Use local exhaust ventilation to control mists or vapors. Additional ventilation or exhaust may be required to maintain concentrations below

recommended exposure limits.

Hygiene measures Wash hands before eating, drinking, smoking or using the

toilet and when leaving work.

Respiratory protectionCarry out a health risk assessment to determine personal

protection equipment that is necessary to avoid contact and

exposure and that is appropriate to the job.

Hand protection Wear PVC or nitrile rubber gloves.

Eye protection Wear safety glasses or full face shield if splashes are likely to

occur.

Body protection Minimise all forms of skin contact, Wear overalls to minimise

contamination of personal clothing. Long sleeve shirt is recommended.. Launder overalls and undergarments before

use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state Liquid at ambient temperature.

Colour Dark Brown Liquid

Odour Characteristic aromatic

Initial boiling point Expected to be around 140 °C.

Solubility in solvents Soluble in organic solvents/petroleum solvents

Solubility in water Insoluble

Kinematic Viscosity at 40°C, cSt 16.09 (typical)

Specific gravity, 29.5 0.85 (typical)

Flash point, °C (COC) 182 min.

MAK RUSTROL 164

BHARAT PETROLEUM CORPORATION LTD.
PAGE 3 OF 5

10. STABILITY/REACTIVITY

Stability Stable

Conditions to avoid Extremes of temperature and direct sunlight

Materials to avoid Strong oxidizing agents

Hazardous decomposition products Hazardous decomposition products are not expected to form

during normal storage.

11 TOXICOLOGICAL INFORMATION

Acute toxicity - Inhalation Not considered to be Inhalation hazard under normal

conditions of use.

Eye Irritation Expected to be slightly irritant

Skin irritation Expected to be slightly irritant, prolonged or repeated skin

contact may cause dermatitis.

Respiratory Irritation If mists are inhaled, slight irritation of the respiratory tract

may occur

Skin Sensitization Not expected to be a skin sensitizer

12. ECOLOGICAL INFORMATION

Basis of assessment Ecotoxicological data have not been determined specifically

for this product. Information given is based on the knowledge of the components and the ecotoxicology of similar products.

Mobility Liquid under most environmental conditions.

Persistence/degradability Not readily biodegradable. Major constituents are expected to

inherently biodegradable, but the product contains components

that may persist in the environment.

Bioaccumulation Has the potential to bioaccumulate

13. DISPOSAL CONSIDERATIONS

Waste disposal Used or waste oil should be recycled or disposed of in

accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the contractor to deal satisfactorily with used oil should be

established beforehand.

Product disposal As for waste disposal.

Container disposal 200 litre drums should be drained and returned to the supplies

or sent to a drum reconditioner without removing or defacing

marking or labels.

MAK RUSTROL 164 BHARAT PETROLEUM CORPORATION LTD. PAGE 4 OF 5

14. TRANSPORT INFORMATION

Not dangerous for conveyance under UN, IMO, ADR/RID and IATA/ICAO codes.

15. REGULATORY INFORMATION

EC Classification Classified as Class-B Category as per petroleum rules

16. OTHER INFORMATION

Compiled By P&AD Department,

Bharat Petroleum Corporation Limited, "A" Installation, Sewree (East),

Mumbai - 400 015.

Technical Contact No. 91 - 22 - 24176354

Fax 9122 – 24166512 24182511

This data sheet and the Health, Safety and Environmental information are considered to be accurate as of the date specified below. We have reviewed any information contained herein, which we received from sources outside BPCL. However, no warranty or representation, express or implied is made as to the accuracy or completeness of the data and information contained in this data sheet.

Health & Safety precautions and environment advice noted in this data sheet may not be accurate for all individuals' and/ or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as a permission, recommendation or authorization given to practice any patent invention without a valid license. BPCL shall not be responsible for any damage or injury resulting from abnormal use of material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material.