1. IDENTIFICATION OF THE SU Material Name Uses	:	TANCE/PREPARATION AND COMPANY/UNDERTAKING Shell Gadus S2 OG 80 Automotive and industrial grease.
Product Code	:	001D8496
Manufacturer/Supplier	:	Shell India Markets Private Limited 2nd Floor, Campus 4A RMZ Millenia Park 143 Dr. MGR Road, Perungudi CHENNAI 600096 India
Telephone Fax		(+91) 04443450000 (+91) 04443451516
Emergency Telephone Number	:	+91 22 6516 1058

2. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture Description

: A lubricating grease consisting of petroleum resins, highly refined mineral oil, synthetic hydrocarbons and additives.

Chemical Identity	CAS	EINECS	Symbol(s)	R-phrase(s)	Conc.
Dialkyl polysulphide	68937-96-2	273-103-3	Xi	R43; R53	< 5.00 %
Amine phosphate	91745-46-9	294-716-2	Xn, Xi, N	R22; R41; R43; R51/53	< 2.50 %

Additional Information : The highly refined mineral oil contains <3% (w/w) DMSOextract, according to IP346. Refer to chapter 16 for full text of EC R-phrases.

3. HAZARDS IDENTIFICATION		
EC Classification	:	Not classified as dangerous under EC criteria.
Health Hazards	:	Not expected to be a health hazard when used under normal conditions. Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis. High-pressure injection under the skin may cause serious damage including local necrosis. Used grease may contain harmful impurities.
Signs and Symptoms	:	Local necrosis is evidenced by delayed onset of pain and tissue damage a few hours following injection. Oil acne/folliculitis signs and symptoms may include formation of

Safety Hazards Environmental Hazards	:	black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea. Not classified as flammable but will burn. Not classified as dangerous for the environment.
4. FIRST AID MEASURES		
General Information	:	Not expected to be a health hazard when used under normal conditions.
Inhalation	:	No treatment necessary under normal conditions of use. If
		symptoms persist, obtain medical advice.
Skin Contact	:	Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention. When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait for symptoms to develop. Obtain medical attention even in the absence of apparent wounds.
Eye Contact	:	Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention.
Ingestion	:	In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
Advice to Physician	:	Treat symptomatically. High pressure injection injuries require prompt surgical intervention and possibly steroid therapy, to minimise tissue damage and loss of function. Because entry wounds are small and do not reflect the seriousness of the underlying damage, surgical exploration to determine the extent of involvement may be necessary. Local anaesthetics or hot soaks should be avoided because they can contribute to swelling, vasospasm and ischaemia. Prompt surgical decompression, debridement and evacuation of foreign material should be performed under general anaesthetics, and wide exploration is essential.

5. FIRE FIGHTING MEASURES

Clear fire area of all non-emergency personnel.

Specific Hazards	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.
Suitable Extinguishing Media Unsuitable Extinguishing	:	Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only. Do not use water in a jet.
Media Protective Equipment for Firefighters	:	Proper protective equipment including breathing apparatus must be worn when approaching a fire in a confined space.

6. ACCIDENTAL RELEASE MEASURES

Avoid contact with spilled or released material. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. See Chapter 13 for information on disposal. Observe the relevant local and international regulations.

Protective measures	:	Avoid contact with skin and eyes. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or
Clean Up Methods	:	other appropriate barriers. Shovel into a suitable clearly marked container for disposal or reclamation in accordance with local regulations.
7. HANDLING AND STORAGE		
General Precautions Handling	:	Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material. Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or
Storage	:	cleaning materials in order to prevent fires. Keep container tightly closed and in a cool, well-ventilated place. Use properly labelled and closeable containers. Store at ambient temperature.
Recommended Materials	:	For containers or container linings, use mild steel or high density polyethylene.
Unsuitable Materials	:	PVC.
Additional Information	:	Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

If the American Conference of Governmental Industrial Hygienists (ACGIH) value is provided on this document, it is provided for information only.

Occupational Exposure Limits

Material	Source	Туре	ppm	mg/m3	Notation
Oil mist, mineral	ACGIH	TWA(Inhala ble fraction.)		5 mg/m3	
	IN OEL	TWA(Mist.)		5 mg/m3	
	IN OEL	STEL(Mist.)		10 mg/m3	

Additional Information

: Due to the product's semi-solid consistency, generation of mists and dusts is unlikely to occur.

Biological Exposure Index (BEI) - See reference for full details No biological limit allocated.

Exposure Controls	:	The level of protection and types of controls necessary will vary	
-------------------	---	---	--

Personal Protective Equipment	 depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations. Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated. Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.
Respiratory Protection	No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapours [boiling point >65°C(149 °F)].
Hand Protection	 Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognise that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time may be acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material.
Eye Protection	: Wear safety glasses or full face shield if splashes are likely to occur.
Protective Clothing	: Skin protection not ordinarily required beyond standard issue work clothes.
Monitoring Methods	: Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate. Validated exposure measurement methods should be applied by a competent person and samples

Material Safety Data Sheet

	analysed by an accredited laboratory. Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.
Environmental Exposure Controls	 National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/ Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/ Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/ Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany. http://www.dguv.de/inhalt/index.jsp L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil Minimise release to the environment. An environmental assessment must be made to ensure compliance with local environmental legislation.
9. PHYSICAL AND CHEMICAL	PROPERTIES
Appearance Odour pH Initial Boiling Point and Boiling Range Pour point Flash point Upper / lower Flammability or Explosion limits Auto-ignition temperature Vapour pressure Specific gravity Density Water solubility Solubility in other solvents n-octanol/water partition coefficient (log Pow) Dynamic viscosity Kinematic viscosity Vapour density (air=1) Electrical conductivity Evaporation rate (nBuAc=1)	 Black. Semi-solid at room temperature. Slight hydrocarbon. Not applicable. Data not available Data not available > 130 °C / 266 °F (COC) Typical 1 - 10 %(V) (based on mineral oil) > 320 °C / 608 °F < 0.5 Pa at 20 °C / 68 °F (estimated value(s)) Typical 1.018 at 15 °C / 59 °F Typical 1,018 kg/m3 at 15 °C / 59 °F Negligible. Data not available > 6 (based on information on similar products) Data not available Not applicable. > 1 (estimated value(s)) This material is not expected to be a static accumulator. Data not available
· · · ·	
10. STABILITY AND REACTIVI Stability Conditions to Avoid Materials to Avoid Hazardous Decomposition Products	 FY Stable. Extremes of temperature and direct sunlight. Strong oxidising agents. Hazardous decomposition products are not expected to form during normal storage.

onents and the
ia
is
than for
/kg , Rat
/kg , Rabbit
er normal
epeated skin
res of the skin
i.
on.
ation of
is product does
ergic skin
lphide, Amine
ins mineral oils
al skin-painting
sified as
esearch on
carcinogen.
card

matchai	•	our emogemently of assimilation
Highly refined mineral oil	:	ACGIH Group A4: Not classifiable as a human carcinogen.
(IP346 <3%)		
Highly refined mineral oil	:	IARC 3: Not classifiable as to carcinogenicity to humans.
(IP346 <3%)		
Highly refined mineral oil	:	GHS / CLP: No carcinogenicity classification
(IP346 <3%)		

Reproductive and : Developmental Toxicity Additional Information :

: Not expected to be a hazard.

: Used grease may contain harmful impurities that have accumulated during use. The concentration of such harmful impurities will depend on use and they may present risks to health and the environment on disposal. ALL used grease should be handled with caution and skin contact avoided as far as possible. High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.

12. ECOLOGICAL INFORMATION Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

Acute Toxicity Microorganisms Mobility Persistence/degradability Bioaccumulation Other Adverse Effects		Poorly soluble mixture. May cause physical fouling of aquatic organisms. Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l (to aquatic organisms) LL/EL50 expressed as the nominal amount of product required to prepare aqueous test extract. Mineral oil is not expected to cause any chronic effects to aquatic organisms at concentrations less than 1 mg/l. Data not available Semi-solid under most environmental conditions. Sinks in water. If it enters soil, it will adsorb to soil particles and will not be mobile. Expected to be not readily biodegradable. Major constituents are expected to be inherently biodegradable, but the product contains components that may persist in the environment. Contains components with the potential to bioaccumulate. Product is a mixture of non-volatile components, which are not expected to be released to air in any significant quantities. Not expected to have ozone depletion potential, photochemical ozone creation potential or global warming potential.
 13. DISPOSAL CONSIDERATION Material Disposal Container Disposal Local Legislation 	NS :	Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses. Dispose in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.

14. TRANSPORT INFORMATION

Land (as per ADR classification): Not regulated

This material is not classified as dangerous under ADR regulations.

IMDG

This material is not classified as dangerous under IMDG regulations.

IATA (Country variations may apply)

This material is either not classified as dangerous under IATA regulations or needs to follow country specific requirements.

Additional Information : MARPOL Annex 1 rules apply for bulk shipments by sea.

15. REGULATORY INFORMATION

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

EC Classification EC Symbols EC Risk Phrases EC Safety Phrases Chemical Inventory Status	:	Not classified as dangerous under EC criteria. No Hazard Symbol required Not classified. Not classified.
EINECS		All components
EINEGO	•	listed or polymer
		exempt.
TSCA	:	All components
		listed.
Sensitiser not sufficient to classify	:	Contains dialkylpolysulphide. Contains amine phosphate. May produce an allergic reaction.
Other Information	:	The Manufacture, Storage and Import of Hazardous Chemicals Rules 1989 (amended version issued 2000). The Factories Act, 1948, The Second Schedule: Permissible levels of certain chemical substances in work environment, as amended through 1987. India Central motor Vehicles (Amendment) Rules 1993.

16. OTHER INFORMATION

R-phrase(s)

R22 R41 R43 R51/53 R53	Not classified. Harmful if swallowed. Risk of serious damage to eyes. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. May cause long-term adverse effects in the aquatic environment.			
SDS Version N	umber	: 1.0		
SDS Effective	Date :	: 19.12.2012		
SDS Revisions	i :	: A vertical bar () in the left margin indicates an amendment		
SDS Distribution	on :	from the previous version. The information in this document should be made available to		
Disclaimer	:	all who may handle the product.This information is based on our current knowledge and is intended to describe the product for the purposes of health,		

safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.