

**TOTAL**

Safety Data Sheet

Product name :**STATERMIC XHT**

Page : 1/5

SDS n° :35845-33

Version :2.02

Version of : 2008-11-09

This sheet supersedes the one dated : 2008-01-31

PRODUCT LABELS

LABELLING (standard or EU):

Not concerned

R-phrases :

None

S-phrases :

None

TRANSPORT LABELLING:

Not applicable.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY UNDERTAKING

Name of the product :

STATERMIC XHT

Code No. :

HNN

Product application :

Lubricating grease

Supplier :

TOTAL LUBRIFIANTS
562 avenue du Parc de l'Ile
92029 Nanterre CEDEX
Tel: +33 (0)1 41 35 40 00
Fax: +33 (0)1 41 35 84 71
rm.msds-lubs@total.com

See local details at end of sheet :

2. HAZARDS IDENTIFICATION

Health effects :

This product does not present a danger of acute intoxication.

Environmental impact :

Do not discharge this product into the environment.

Physico-chemical hazards :

No specific risk of fire or explosion under normal conditions of use

3. COMPOSITION/INFORMATION ON INGREDIENTS

PREPARATION

Chemical nature :

The product is made of fluorosilicone oils and P.T.F.E. polymer.

Composition comments :

Substances contributing to hazards :
None to our knowledge

4. FIRST AID MEASURES

IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.

Inhalation :

Inhalation of heavy concentrations of vapour, fumes or spray, may cause mild irritation of the throat.
Transport the person into fresh air, keep warm and allow to rest.

Ingestion :

Possible risk of vomiting and diarrhoea.
Do not induce vomiting to avoid the risk of aspiration into the respiratory tract.

Skin contact :

Immediately remove all soiled or stained clothing.
Wash the affected area immediately and repeatedly with soap and water.
If the skin is exposed to high-pressure spray, the product may enter the human body.
In all such cases the affected person must be taken to hospital, even if no sign of injury can be detected.

Eye contact :

Keep eyes open and rinse immediately and repeatedly with water for at least 15 minutes.



TOTAL

Safety Data Sheet

Product name :

STATERMIC XHT

Page : 2/5

SDS n° :35845-33

Version :2.02

Version of : 2008-11-09

This sheet supersedes the one dated : 2008-01-31

5. FIRE FIGHTING MEASURES

Flash point:
See heading 9

Extinguishing media :

- suitable:
Foam, carbon dioxide (CO2), powder.
- not recommended:
Do not use water jets (stick jets) for extinguishing fire, as this may help the spread of flames.

Specific hazards :

Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled.

Protective measures for firefighters :

Insulated breathing apparatus must be worn in confined premises with heavy concentrations of fumes and gases.

Other :

All combustion residues and contaminated water from fire-fighting should be disposed of according to local regulations.

6. ACCIDENTAL RELEASE MEASURES

See sections 8 and 13.

Personal protection :

Ensure good ventilation.
Remove sources of ignition. Do not smoke.

After spillage / leakage :

- On land:
Surfaces on which the product has been spilled may become slippery.
Do not allow the product to enter sewers or rivers or contaminate the soil.
Recover with mechanical means such as pumps and skimmers.
Contain and collect the spilled product with sand or any other inert absorbant material.
In case of spillage, contact the competent authorities if the situation cannot be brought under control rapidly and efficiently.
- On water:
Floating absorbant material, then mechanical recovery.
If the product is spilt into rivers or sewers, notify the authorities of the possible presence of surface effluent.

7. HANDLING AND STORAGE

HANDLING :

Prevention of user exposure :

Ventilate extensively if the formation of vapours, fumes, mists or aerosol is a risk.
Make all the necessary arrangements in order to reduce exposure risk, notably to products in use or to wastes.
Keep away from combustible substances; keep away from food and beverages.

Prevention of fire and explosion :

Empty containers may contain flammable or explosive vapours.
There is a fire hazard associated with rags, paper or any other material used to remove spills which become soaked with product.
Avoid accumulation of these: they are to be disposed off safely after use.

Precautions :

Avoid static electricity build up with connection to earth.
Set up machinery and equipment so as to avoid the risk of accidental spills or splashes onto hot machine parts and electrical contacts (on joint failure, for example).

STORAGE :

Technical measures :

Make the necessary arrangements to prevent water and soil pollution.



Safety Data Sheet

Product name :

STATERMIC XHT

Page : 3/5

SDS n° :35845-33

Version :2.02

Version of : 2008-11-09

This sheet supersedes the one dated : 2008-01-31

Storage precautions :

- Suitable:
Store at ambient temperature, protected against contact with water and moisture, and away from any source of ignition.
Keep containers closed when not in use
- To be avoided:
Do not store exposed to the elements.

Incompatible products :

Dangerous reaction with strong oxidizing agents.

Packaging materials :

- Recommended:
Use only hydrocarbon-resistant containers, joints, pipes, etc.
Keep in original container if possible.
Otherwise, transfer all indications on the regulatory label to the new container.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Technical measures :

Use the product in a properly ventilated atmosphere.
When working on enclosed place (tanks, reservoirs...), make sure that atmosphere is not suffocating and/or wear recommended equipment.

Occupational exposure limit :

. oil mist : 10mg/m3, for 15 minutes
. oil mist : 5mg/m3, for 8 hours

Respiratory protection :

It is not necessary in normal conditions.
In case of vapours or sprays formation:
Combined gas cartridge (organic gases and dust, filter A/P2).

Hand protection :

The demands on the gloves are determined by the conditions in practice (e.g. multiple use, mechanical load, temperature, strength and duration of exposition). Before choosing suitable gloves, it is recommended that the user tests the gloves. The break through times of the same type of glove of different manufacturers can be very different - even if the layer thickness is similar. Therefore the break through times have to be found out from the manufacturer of the protective gloves themselves.
Impermeable hydrocarbon-proof gloves.
recommended material: nitrile , neoprene.

Eye protection :

Goggles, in case of risk of splashing.

Skin and body (other than the hands) protection :

As required, wear a face mask, hydrocarbon-proof clothing, and safety boots (when handling drums).
Don't wear rings, watches or anything similar which can retain the product and may give rise to skin conditions.

Hygienic work practices :

Avoid prolonged and repeated contact with the skin, especially with used or waste product
Immediately remove all soiled or stained clothing.
If the product comes into contact with the skin, wash the affected area immediately and copiously with soap and water.
Do not use abrasives, solvents or fuels.
Do not dry hands with rags that have been contaminated with product.
Do not put product contaminated rags into workwear pockets.
Do not eat, drink or smoke whilst handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance :

Pasty

Colour :

White to light yellow

Odour :

Characteristic

Density/specific gravity :

1800 kg/m3
Temperature (°C) 15

**TOTAL**

Safety Data Sheet

Product name :**STATERMIC XHT**

Page : 4/5

SDS n° :35845-33

Version :2.02

Version of : 2008-11-09

This sheet supersedes the one dated : 2008-01-31

Comments on flash points :	@@@Not determined@@@
Température d'auto-inflammation :	Refined base oil > 300 °C (ASTM E 659)
Comments on autoignition temperature :	This temperature may be significantly lower under particular conditions (slow oxidation on finely divided materials...).
Comments on explosivity :	Not applicable
Temperatures at phase change :	Dropping point: 300 ° C
Solubility :	- in water : Insoluble and immiscible. - in organic solvents : Soluble in many common solvents.

10. STABILITY AND REACTIVITY

Stability :	The product is stable at normal storage, handling and use temperatures.
Conditions to avoid :	Heat, sparks, ignition points, flames, static electricity.
Materials to avoid :	Avoid contact with strong oxidizers
Hazardous decomp. products :	Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot.

11. TOXICOLOGICAL INFORMATION

Acute toxicity / Local effect :	
Inhalation, comments:	Inhalation of high concentrations of vapour or aerosols may cause irritation of the upper respiratory tract.
Skin contact, comments:	If the skin is exposed to high-pressure spray, the product may enter the body. In all such cases the affected person must be taken to hospital, even if no sign of injury can be detected
Ingestion, comments:	In case of ingestion of small quantities, no important effect observed. in case of ingestion of larger amounts: abdominal pain, diarrhea, ...

CHRONIC TOXICITY OR LONG-TERM TOXICITY :

Skin contact :	Characteristic skin affections (oil blisters) may develop following prolonged and repeated exposure through contact with stained clothing
Sensitization :	To our knowledge, the product does not cause aggravated sensitivity.

12. ECOLOGICAL INFORMATION

Comments about ecotoxicity :	Experimental data on the finished product are not available. It is considered to present a little danger for aquatic life. no information available for used product
Mobility :	- Air: there is a slow loss by evaporation. - Soil: Given its physical and chemical characteristics, the product has no soil mobility. - Water: The product is insoluble; it spreads on the surface of the water
Persistence and degradability :	No experimental information about the finished product. However the "mineral oil" fraction of the new product is intrinsically biodegradable.

**TOTAL**

Safety Data Sheet

Product name :**STATERMIC XHT**

Page : 5/5

SDS n° :35845-33

Version :2.02

Version of : 2008-11-09

This sheet supersedes the one dated : 2008-01-31

13. DISPOSAL CONSIDERATIONS

Waste disposal :

Dispose of in a safe manner, in accordance with local regulations.
If need be, collection by an authorised waste contractor and regeneration or incineration at an approved installation.

Waste class :

The waste classification mentioned here represents only a recommendation. The waste producer is responsible for the correct specification of the waste. The specification of the waste classification should be in arrangement with the authorised waste disposal company.
The waste classification is dependant on the composition of the product at the time of disposal.
12 01 12

Disposal of contaminated packaging :

Proceed in compliance with the prevailing regulations.

14. TRANSPORT INFORMATION

Not concerned by the transport regulations below.

Road (ADR) / Rail (RID) :

Transport by barge (ADNR) :

Marine (IMO-IMDG) :

Air (ICAO/IATA) :

15. REGULATORY INFORMATION

Not applicable

Risk phrases :

None

Safety phrases :

None

EU directives :

Hazardous preparations directive 1999/45/EC modified (Directive 2001/60/EC).

Social Security code :

Table of occupational illnesses and diseases No. 36
- Art. L 461-6, Art. D.461-1, annexe A, n° 601

Labor code :

- Art. R 241-50, decree of 07.11.1977 (special medical surveillance).

16. OTHER INFORMATION

Revision date:

2008-11-09

Supersedes the data sheet of:

2008-01-31

* Information revised since the previous version of the SDS :

SDS No. :

ZZ-704177

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

STATERMIC XHT



Grease



TOTAL

Synthetic grease with Fluor compounds.

APPLICATIONS

- Special grease formulated with fluorinated components for use in applications working under high temperatures and medium to heavy loads.

SPECIFICATIONS

- ISO 6743-9: L-XBGDB-2
- DIN 51502: KFKP2U-25

ADVANTAGES

- **STATERMIC XHT** has been formulated with synthetic components which reduce the friction coefficient of most plastic and metal materials.
- The rheology of the structure has been adapted in such a way to obtain a extended application at temperatures up to 250 °C with peak temperatures up to 270 °C. The starting torque at - 25 °C is very low.
- The stability of the chemical structure of the components ensure a compatibility with most of the plastic and metal materials used in the industry (except fluorinated components).
- The very high cohesion of the structure, its excellent resistance to temperature and chemical products, its low volatility contributes to a very long life time of the **STATERMIC XHT**.

TYPICAL CHARACTERISTICS	METHODS	UNITS	STATERMIC XHT
Color / appearance			White/Homogeneous
Base oil viscosity at 40 °C	ASTM D 445	mm ² /s	147
Worked penetration W 60 at 25°C	ASTM D 217	mm/10	265 - 295
Worked penetration 100.000 strokes	ASTM D 217	change	< 15
Dropping point	NF T 60 102	°C	> 300
Oil separation 149°C/30 Hrs.	FTMS 791 - 321	%	< 6
Evaporation 149 °C/22 hrs./120 l/hr air	ASTM D 972	%	< 0.4
Four ball weld load	ASTM D 2596	daN	800
Operating temperature range		°C	- 25 to 250

Above characteristics are mean values given as an information.

TOTAL LUBRIFIANTS
Industrie & Spécialités
19-07-2001
STATERMIC XHT
1/1



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.
A material safety data sheet conforming to the regulations in use in the E.C. is obtainable via your commercial adviser www.quick-fds.com.