

Revision Date: 07/20/2012 Print Date: 6/9/2015 MSDS Number: R0326850 Version: 1.8

PREMIUM BLUE® GEO SAE 15W40 ENGINE OIL 3498

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Ashland P.O. Box 2219 Columbus, OH 43216	Regulatory Information Number Telephone Emergency telephone number	1-800-325-3751 614-790-3333 1-800-ASHLAND (1-800-274- 5263)
Product name	PREMIUM BLUE® GEO SAE 15W40 ENGINE OIL	
Product code Product Use Description	3498 Engine, gear & lubricating oil.	

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid, amber

CAUTION! PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION.

Potential Health Effects

Exposure routes

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

Eye contact

May cause mild eye irritation. Symptoms include stinging, tearing, and redness.

Skin contact

May cause slight skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, and drying and cracking of skin, skin burns, and other skin damage.

Ingestion

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful.

Page 1 / 10



Revision Date: 07/20/2012 Print Date: 6/9/2015 MSDS Number: R0326850 Version: 1.8

PREMIUM BLUE® GEO SAE 15W40 ENGINE OIL 3498

Inhalation

It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

No data

Symptoms No data

Target Organs

No data

Carcinogenicity

This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA).

Reproductive hazard

No data

3. COMPOSITION/INFORMATION ON INGREDIENTS

WHMIS hazardous composition: No ingredients are hazardous according to the CPR criteria.

4. FIRST AID MEASURES

Eyes

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

Skin

Page 2 / 10



PREMIUM BLUE® GEO SAE 15W40 ENGINE OIL 3498

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Notes to physician

Hazards: Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

Treatment: No information available.

5. FIREFIGHTING MEASURES

Suitable extinguishing media

Dry chemical, Carbon dioxide (CO2), Water spray

Hazardous combustion products

carbon dioxide and carbon monoxide, Hydrocarbons

Precautions for fire-fighting

Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). DO NOT direct a solid stream of water or foam into hot, burning pools of liquid since this may cause frothing and increase fire intensity. Frothing can be violent and possibly endanger any firefighter standing too close to the burning liquid. Use water spray to cool fire exposed containers and structures

Page 3 / 10

Page: 3

Revision Date: 07/20/2012 Print Date: 6/9/2015 MSDS Number: R0326850 Version: 1.8



Revision Date: 07/20/2012 Print Date: 6/9/2015 MSDS Number: R0326850 Version: 1.8

PREMIUM BLUE® GEO SAE 15W40 ENGINE OIL 3498

until fire is out if it can be done with minimal risk. Avoid spreading burning material with water used for cooling purposes.

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions

Prevent spreading over a wide area (e.g. by containment or oil barriers). Do not let product enter drains. Do not flush into surface water or sanitary sewer system.

Methods for cleaning up

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Other information

Comply with all applicable federal, state, and local regulations.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed.

Storage

Store in a cool, dry, ventilated area.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Page 4 / 10



PREMIUM BLUE® GEO SAE 15W40 ENGINE OIL 3498

DISTILLATES (PETROLEUM), SOLVENT-64742-65-0 **DEWAXED HEAVY PARAFFINIC** OEL (QUE) time weighted average 5 mg/m3 Mist. OEL (QUE) Short term exposure limit 10 mg/m3 Mist. CAD AB OEL time weighted average 5 mg/m3Mist. CAD AB OEL Short term exposure limit 10 mg/m3 Mist. CAD BC OEL time weighted average 0.2 mg/m3 Mist. CAD BC OEL time weighted average 1 mg/m3Mist. CAD MB OEL time weighted average 5 mg/m3 Inhalable fraction. CAD ON OEL time weighted average 5 mg/m3Mist. CAD ON OEL Short term exposure limit 10 mg/m3 Mist.

General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Eye protection

Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection

Wear normal work clothing including long pants, long-sleeved shirts and foot covering to prevent direct contact of the product with the skin. Launder clothing before reuse. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use. Wear resistant gloves (consult your safety equipment supplier).

Respiratory protection

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by airpurifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential

Page 5 / 10

Revision Date: 07/20/2012 Print Date: 6/9/2015 MSDS Number: R0326850 Version: 1.8



Revision Date: 07/20/2012 Print Date: 6/9/2015 MSDS Number: R0326850 Version: 1.8

PREMIUM BLUE® GEO SAE 15W40 ENGINE OIL 3498

for uncontrolled release, exposure levels are not known or any other circumstances where an airpurifying respirator may not provide adequate protection.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid	
Colour	amber	
Odour	mild	
Boiling point/boiling range	(>)424 °F / 218 °C @ 760.00 mmHg	
Flash point	> 390 °F / > 199 °C Closed Cup	
Density	0.873 g/cm3 @ 60.01 °F / 15.56 °C	
Water solubility	partly miscible	
Auto-ignition temperature	no data available	
Viscosity, kinematic	(+/- 1.51)14 mm2/s	

10. STABILITY AND REACTIVITY

Stability

Stable.

Conditions to avoid

None known.

Incompatible products

Strong oxidizing agents

Hazardous decomposition products

carbon dioxide and carbon monoxide, Hydrocarbons

Hazardous reactions

Product will not undergo hazardous polymerization.



Revision Date: 07/20/2012 Print Date: 6/9/2015 MSDS Number: R0326850 Version: 1.8

PREMIUM BLUE® GEO SAE 15W40 ENGINE OIL 3498

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity

Acute oral toxicity -	: no data available	
Product		

Acute inhalation toxicity

Acute inhalation toxicity - : no data available Product

Acute dermal toxicity

Acute dermal toxicity - : no data available Product

Acute toxicity (other routes of administration)

Acute toxicity (other : no data available routes of administration)

12. ECOLOGICAL INFORMATION

Biodegradability

Biodegradability - Product : no data available

Bioaccumulation

Bioaccumulation - Product	: no data available	
----------------------------------	---------------------	--

Ecotoxicity effects

Toxicity to fish

kicity to fish - Product

Toxicity to daphnia and other aquatic invertebrates

Toxicity to daphnia and : no data available other aquatic invertebrates - Product

Page 7 / 10



Revision Date: 07/20/2012 Print Date: 6/9/2015 MSDS Number: R0326850 Version: 1.8

PREMIUM BLUE® GEO SAE 15W40 ENGINE OIL 3498

Toxicity to algae

Toxicity to algae -	: no data available	
Product		

Toxicity to bacteria

Toxicity to bacteria -	: no data available
Product	

13. DISPOSAL CONSIDERATIONS

Waste disposal methods

Dispose of in accordance with all applicable local, state and federal regulations.

14. TRANSPORT INFORMATION

REGULATION

ID	PROPER SHIPPING NAME	*HAZARD	SUBSIDIARY	PACKING	MARINE
NUMBER		CLASS	HAZARDS	GROUP	POLLUTANT
					/ LTD. QTY.
U.S. DOT - ROAD					

Not dangerous goods

U.S. DOT - RAIL

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TRANSPORT CANADA - ROAD

Not dangerous goods



PREMIUM BLUE® GEO SAE 15W40 ENGINE

TRANSPORT CANADA - RAIL

OIL 3498

Not dangerous goods

TRANSPORT CANADA - INLAND WATERWAYS

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

Not dangerous goods

***ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

15. REGULATORY INFORMATION

WHMIS Classification

Not Rated

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

Canadian National Pollutant Release Inventory (NPRI)

Canadian National Pollutant Release Inventory (NPRI): No component is listed on NPRI.

Notification status

US. Toxic Substances Control Act	y (positive listing)
----------------------------------	----------------------

Revision Date: 07/20/2012 Print Date: 6/9/2015 MSDS Number: R0326850 Version: 1.8



Revision Date: 07/20/2012 Print Date: 6/9/2015 MSDS Number: R0326850 Version: 1.8

PREMIUM BLUE® GEO SAE 15W40 ENGINE OIL 3498

Canada. Canadian Environmental Protection Act (CEPA).	y (positive listing)
Domestic Substances List (DSL). (Can. Gaz. Part II, Vol. 133)	
Australia. Industrial Chemical (Notification and Assessment)	y (positive listing)
Act	
New Zealand. Inventory of Chemicals (NZIoC), as published	n (Negative listing)
by ERMA New Zealand	
Japan. Kashin-Hou Law List	n (Negative listing)
Korea. Toxic Chemical Control Law (TCCL) List	y (positive listing)
Philippines. The Toxic Substances and Hazardous and Nuclear	y (positive listing)
Waste Control Act	
China. Inventory of Existing Chemical Substances	y (positive listing)

	HMIS	NFPA
Health	1	1
Flammability	1	1
Physical hazards	0	
Instability		0
Specific Hazard		

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).