ASHLAND	Page: 1
SAFETY DATA SHEET	Revision Date: 05/22/2015
	Print Date: 6/30/2015
	SDS Number: R0326850
PREMIUM BLUE® GEO SAE 15W40 ENGINE OIL	Version: 1.0
3498	

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : PREMIUM BLUE® GEO SAE 15W40

ENGINE OIL

Recommended use of the chemical and restrictions on use

Use of the Substance/Mixture : Engine, gear & lubricating oil.

Details of the supplier of the safety data	Emergency telephone number
sheet	1-800-ASHLAND (1-800-274-5263)
Ashland	
P.O. Box 2219	Regulatory Information Number
Columbus, OH 43216	1-800-325-3751
United States of America	
	Product Information
	614-790-3333
EHS Customer Requests@ashland.com	
·	

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Skin sensitization : Category 1

GHS Label element

Hazard pictograms :



Signal Word : Warning

Hazard Statements : May cause an allergic skin reaction.

Precautionary Statements : If medical advice is needed, have product container or label at

hand.

Keep out of reach of children. Read label before use.

Prevention:

Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray. Contaminated work clothing must not be allowed out of the

workplace.

Wear protective gloves.

Response:

ASHLAND	Page: 2
SAFETY DATA SHEET	Revision Date: 05/22/2015
	Print Date: 6/30/2015
	SDS Number: R0326850
PREMIUM BLUE® GEO SAE 15W40 ENGINE OIL	Version: 1.0
3498	

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/ attention.

Wash contaminated clothing before reuse.

Disposal:

Dispose of contents/ container to an approved waste disposal

plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

Hazardous components

Chemical Name	CAS-No.	Classification	Concentration (%)
Calcium long chain alkaryl sulfonate	68610-84-4	Skin Sens. 1; H317	1.09
		Aquatic Chronic 4; H413	

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If breathed in, move person into fresh air.

If unconscious place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Remove contaminated clothing. If irritation develops, get

medical attention.

If on skin, rinse well with water.

First aid is not normally required. However, it is

recommended that exposed areas be cleaned by washing

with soap and water.

Wash contaminated clothing before re-use.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

If eye irritation persists, consult a specialist.

ASHLAND	Page: 3
SAFETY DATA SHEET	Revision Date: 05/22/2015
	Print Date: 6/30/2015
	SDS Number: R0326850
PREMIUM BLUE® GEO SAE 15W40 ENGINE OIL	Version: 1.0
3498	

If swallowed : Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

: No symptoms known or expected. May cause an allergic skin reaction.

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray Foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: carbon dioxide and carbon monoxide

Hydrocarbons sulfur oxides

Specific extinguishing

methods

Product is compatible with standard fire-fighting agents.

Further information : Standard procedure for chemical fires.

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: Use personal protective equipment.

Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

Methods and materials for : Soak up with inert absorbent material (e.g. sand, silica gel,

ASHLAND	Page: 4
SAFETY DATA SHEET	Revision Date: 05/22/2015
	Print Date: 6/30/2015
	SDS Number: R0326850
PREMIUM BLUE® GEO SAE 15W40 ENGINE OIL	Version: 1.0
3498	

containment and cleaning up acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours/dust.

Do not smoke.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Container hazardous when empty.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes.

Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Electrical installations / working materials must comply with

the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Engineering measures : Provide sufficient mechanical (general and/or local exhaust)

ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or

apparent adverse effects.

Personal protective equipment

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Not required under normal conditions of use. Wear splash-

proof safety goggles if material could be misted or splashed

into eyes.

Skin and body protection : Wear as appropriate:

impervious clothing

Safety shoes

ASHLAND	Page: 5
SAFETY DATA SHEET	Revision Date: 05/22/2015
	Print Date: 6/30/2015
	SDS Number: R0326850
PREMIUM BLUE® GEO SAE 15W40 ENGINE OIL	Version: 1.0
3498	

Choose body protection according to the amount and concentration of the dangerous substance at the work place. Discard gloves that show tears, pinholes, or signs of wear. Wear resistant gloves (consult your safety equipment

supplier).

Hygiene measures : Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Colour : amber

Odour : mild

Odour Threshold : No data available

pH : No data available

: No data available

Boiling point/boiling range : > 424 °F / 218 °C

(1013 hPa)

Flash point : $> 390 \, ^{\circ}\text{F} / > 199 \, ^{\circ}\text{C}$

Method: Closed Cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : 0.873 g/cm3 (15.56 °C)

Solubility(ies)

Water solubility : partly miscible

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

ASHLAND	Page: 6
SAFETY DATA SHEET	Revision Date: 05/22/2015
	Print Date: 6/30/2015
	SDS Number: R0326850
PREMIUM BLUE® GEO SAE 15W40 ENGINE OIL	Version: 1.0
3498	

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 114 mm2/s (40 °C)

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Product will not undergo hazardous polymerization.

Conditions to avoid : None known.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

carbon dioxide and carbon monoxide

Sulphur oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of : Inhalation

exposure Skin contact Eye Contact

Ingestion

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks: May cause skin irritation in susceptible persons.

Result: Repeated exposure may cause skin dryness or cracking.

Components:

Calcium long chain alkaryl sulfonate: Result: Possibly irritating to skin

ASHLAND	Page: 7
SAFETY DATA SHEET	Revision Date: 05/22/2015
	Print Date: 6/30/2015
	SDS Number: R0326850
PREMIUM BLUE® GEO SAE 15W40 ENGINE OIL	Version: 1.0
3498	

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

Calcium long chain alkaryl sulfonate: Result: Possibly irritating to eyes

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

Components:

Calcium long chain alkaryl sulfonate:

Assessment: May cause sensitisation by skin contact.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks: No data available

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHANo component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Calcium long chain alkaryl sulfonate:

ASHLAND	Page: 8
SAFETY DATA SHEET	Revision Date: 05/22/2015
	Print Date: 6/30/2015
	SDS Number: R0326850
PREMIUM BLUE® GEO SAE 15W40 ENGINE OIL	Version: 1.0
3498	

Ecotoxicology Assessment

Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.

Persistence and degradability

Components:

No data available

Bioaccumulative potential

Components:

No data available

Mobility in soil

Components:

No data available

Other adverse effects

No data available

Product:

Additional ecological

information

: No data available

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and

federal regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Empty containers should be taken to an approved waste

handling site for recycling or disposal. Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

REGULATION							
ID NUMBER	PROPER SHIPPING NAME	*HAZARD	SUBSIDIARY	PACKING	MARINE		
		CLASS	HAZARDS	GROUP	POLLUTANT /		
					LTD. QTY.		

Revision Date: 05/22/2015
Print Date: 6/30/2015
SDS Number: R0326850
Version: 1.0

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

ASHLAND	Page: 10
SAFETY DATA SHEET	Revision Date: 05/22/2015
	Print Date: 6/30/2015
	SDS Number: R0326850
PREMIUM BLUE® GEO SAE 15W40 ENGINE OIL	Version: 1.0
3498	

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : Acute Health Hazard

SARA 313 Component(s)SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Pennsylvania Right To Know

HEAVY PARAFFINIC DISTILLATE 64742-54-7 90.00 - 100.00 % Highly refined Mineral Oil (C15 -C50) Not Assigned 1.00 - 5.00 %

New Jersey Right To Know

HEAVY PARAFFINIC DISTILLATE 64742-54-7 90.00 -100.00 % Highly refined Mineral Oil (C15 -C50) Not Assigned 1.00 - 5.00 % POLYOLEFIN POLYAMINE SUCCINIMIDE. Not Assigned 1.00 - 5.00 % **BORATED** HYDROCARBON POLYMER Not Assigned 1.00 - 5.00 % 68610-84-4 Calcium long chain alkaryl sulfonate 1.00 - 5.00 % POLYOLEFIN POLYAMINE SUCCINIMIDE, Not Assigned 1.00 - 5.00 %

POLYOL

California Prop 65 This product does not contain any chemicals known to State

of California to cause cancer, birth defects, or any other

reproductive harm.

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL.

AUSTR : On the inventory, or in compliance with the inventory

ENCS : Not in compliance with the inventory

KECL : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : Not in compliance with the inventory

Inventories


AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

ASHLAND	Page: 11
SAFETY DATA SHEET	Revision Date: 05/22/2015
	Print Date: 6/30/2015
	SDS Number: R0326850
PREMIUM BLUE® GEO SAE 15W40 ENGINE OIL	Version: 1.0
3498	

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 05/22/2015



NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements referred to under sections 2 and 3.

H317 May cause an allergic skin reaction.

H413 May cause long lasting harmful effects to aquatic life.

Sources of key data used to compile the Safety Data Sheet
Ashland internal data including own and sponsored test reports
The LINECE administers regional agreements implementing barrow

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet:

ACGIH: American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

ASHLAND	Page: 12
SAFETY DATA SHEET	Revision Date: 05/22/2015
	Print Date: 6/30/2015
	SDS Number: R0326850
PREMIUM BLUE® GEO SAE 15W40 ENGINE OIL	Version: 1.0
3498	

H-statement : Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic

PPE: Personal Protective Equipment STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV: Threshold Limit Value TWA: Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

DOT: Department of Transportation

FIFRA: Federal Insecticide, Fungicide, and Rodenticide Act HMIRC: Hazardous Materials Information Review Commission

HMIS: Hazardous Materials Identification System NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety and Health Administration

PMRA: Health Canada Pest Management Regulatory Agency

RTK: Right to Know

WHMIS: Workplace Hazardous Materials Information System