ASHLAND	Page: 1
SAFETY DATA SHEET	Revision Date: 05/21/2015
	Print Date: 6/30/2015
	SDS Number: 000000204611
Valvoline™ ULTRAMAX TRANS & DRIVE TRAIN TO-4M	Version: 1.0
786016	

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Valvoline™ ULTRAMAX TRANS & DRIVE TRAIN TO-4M

Recommended use of the chemical and restrictions on use

Use of the Substance/Mixture : Lubricant

Details of the supplier of the safety data	Emergency telephone number
sheet	1-800-ASHLAND (1-800-274-5263)
Ashland	
P.O. Box 2219	Regulatory Information Number
Columbus, OH 43216	1-800-325-3751
United States of America	
	Product Information
	614-790-3333
EHS Customer Requests@ashland.com	
·	

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Skin sensitization : Category 1

Reproductive toxicity : Category 2

GHS Label element

Hazard pictograms





Signal Word : Warning

Hazard Statements : May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

Precautionary Statements : Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and

understood.

Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

Contaminated work clothing must not be allowed out of the

ASHLAND	Page: 2
SAFETY DATA SHEET	Revision Date: 05/21/2015
	Print Date: 6/30/2015
	SDS Number: 000000204611
Valvoline™ ULTRAMAX TRANS & DRIVE TRAIN TO-4M	Version: 1.0
786016	

workplace.

Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

IF ON SKIN: Wash with plenty of soap and water.

IF exposed or concerned: Get medical advice/ attention.

If skin irritation or rash occurs: Get medical advice/ attention.

Wash contaminated clothing before reuse.

Storage:

Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal

plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

Hazardous components

Chemical Name	CAS-No.	Classification	Concentration (%)
Mineral Oil		Asp. Tox. 1; H304	2.22
DODECYLPHENOL, MIXED ISOMERS (BRANCHED)	74499-35-7	Skin Irrit. 2; H315 Eye Irrit. 2A; H319 Repr. 2; H361 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	0.36
BENZENE, POLYPROPENE DERIVATIVES, SULFONATED, CALCIUM SALTS		Eye Irrit. 2A; H319 Skin Sens. 1; H317	0.36

ASHLAND	Page: 3
SAFETY DATA SHEET	Revision Date: 05/21/2015
	Print Date: 6/30/2015
	SDS Number: 000000204611
Valvoline™ ULTRAMAX TRANS & DRIVE TRAIN TO-4M	Version: 1.0
786016	

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious place in recovery position and seek medical

advice

If symptoms persist, call a physician.

In case of skin contact : Remove contaminated clothing. If irritation develops, get

medical attention.

If on skin, rinse well with water.

First aid is not normally required. However, it is

recommended that exposed areas be cleaned by washing

with soap and water.

Wash contaminated clothing before re-use.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

If eye irritation persists, consult a specialist.

If swallowed : Obtain medical attention.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through

the skin may include:

Fever

stomach or intestinal upset (nausea, vomiting, diarrhea)

irritation (nose, throat, airways)

Cough Headache muscle cramps

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray Foam

Carbon dioxide (CO2)

Dry chemical

ASHLAND	Page: 4
SAFETY DATA SHEET	Revision Date: 05/21/2015
	Print Date: 6/30/2015
	SDS Number: 000000204611
Valvoline™ ULTRAMAX TRANS & DRIVE TRAIN TO-4M	Version: 1.0
786016	

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: carbon dioxide and carbon monoxide

Hydrocarbons Aldehydes

Specific extinguishing

methods

:

Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Ensure adequate ventilation.

Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours/dust.

Do not smoke.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

ısed.

Container hazardous when empty.

ASHLAND	Page: 5
SAFETY DATA SHEET	Revision Date: 05/21/2015
	Print Date: 6/30/2015
	SDS Number: 000000204611
Valvoline™ ULTRAMAX TRANS & DRIVE TRAIN TO-4M	Version: 1.0
786016	

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes.

Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Engineering measures : Provide sufficient mechanical (general and/or local exhaust)

ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or

apparent adverse effects.

Personal protective equipment

Respiratory protection

In the case of vapour formation use a respirator with an

approved filter.

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not

provide adequate protection.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Not required under normal conditions of use. Wear splash-

proof safety goggles if material could be misted or splashed

into eyes.

Skin and body protection : Wear as appropriate:

ASHLAND	Page: 6
SAFETY DATA SHEET	Revision Date: 05/21/2015
	Print Date: 6/30/2015
	SDS Number: 000000204611
Valvoline™ ULTRAMAX TRANS & DRIVE TRAIN TO-4M	Version: 1.0
786016	

impervious clothing Safety shoes

Choose body protection according to the amount and concentration of the dangerous substance at the work place. Discard gloves that show tears, pinholes, or signs of wear. Wear resistant gloves (consult your safety equipment

supplier).

Hygiene measures : Wash hands before breaks and at the end of workday.

When using do not eat or drink. When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Odour : No data available

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : 662 °F / 350 °C

(1,013.333333 hPa)

Calculated Phase Transition Liquid/Gas

Flash point : $> 390 \, ^{\circ}\text{F} / > 199 \, ^{\circ}\text{C}$

Method: Cleveland open cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit : 6 %(V)

GLP: Calculated Explosive Limit

Lower explosion limit : 1 %(V)

GLP: Calculated Explosive Limit

Vapour pressure : 0.1333333 hPa (20 °C)

Calculated Vapor Pressure

Relative vapour density : No data available

Relative density : No data available

Density : 0.872 g/cm3 (20 °C)

Solubility(ies)

Water solubility : No data available

ASHLAND	Page: 7
SAFETY DATA SHEET	Revision Date: 05/21/2015
	Print Date: 6/30/2015
	SDS Number: 000000204611
Valvoline™ ULTRAMAX TRANS & DRIVE TRAIN TO-4M	Version: 1.0
786016	

: No data available Solubility in other solvents

Partition coefficient: n-

octanol/water

: No data available

: No data available Thermal decomposition

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 14.5 mm2/s (100 °C)

: No data available Oxidizing properties

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Product will not undergo hazardous polymerization.

Conditions to avoid None known.

Incompatible materials Strong oxidizing agents

Hazardous decomposition

No hazardous decomposition products are known. products

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of : Inhalation

exposure

Skin contact Eye Contact Ingestion

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks: May cause skin irritation in susceptible persons.

Result: Repeated exposure may cause skin dryness or cracking.

ASHLAND	Page: 8
SAFETY DATA SHEET	Revision Date: 05/21/2015
	Print Date: 6/30/2015
	SDS Number: 000000204611
Valvoline™ ULTRAMAX TRANS & DRIVE TRAIN TO-4M	Version: 1.0
786016	

Components:

DODECYLPHENOL, MIXED ISOMERS (BRANCHED):

Result: Irritating to skin

BENZENE, POLYPROPENE DERIVATIVES, SULFONATED, CALCIUM SALTS:

Result: Possibly irritating to skin

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

DODECYLPHENOL, MIXED ISOMERS (BRANCHED):

Result: Irritating to eyes

BENZENE, POLYPROPENE DERIVATIVES, SULFONATED, CALCIUM SALTS:

Result: Irritating to eyes

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

Components:

BENZENE, POLYPROPENE DERIVATIVES, SULFONATED, CALCIUM SALTS:

Assessment: May cause sensitization by skin contact.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

Components:

DODECYLPHENOL, MIXED ISOMERS (BRANCHED):

Reproductive toxicity - : Suspected of damaging fertility. Suspected of damaging the

Assessment unborn child.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

Mineral Oil:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

Carcinogenicity:

ASHLAND	Page: 9
SAFETY DATA SHEET	Revision Date: 05/21/2015
	Print Date: 6/30/2015
	SDS Number: 000000204611
Valvoline™ ULTRAMAX TRANS & DRIVE TRAIN	Version: 1.0
TO-4M	
786016	

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

DODECYLPHENOL, MIXED ISOMERS (BRANCHED):

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Additional ecological

information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life

with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and

federal regulations.

ASHLAND	Page: 10
SAFETY DATA SHEET	Revision Date: 05/21/2015
	Print Date: 6/30/2015
	SDS Number: 000000204611
Valvoline™ ULTRAMAX TRANS & DRIVE TRAIN TO-4M	Version: 1.0
786016	

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Empty containers should be taken to an approved waste

handling site for recycling or disposal. Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD	SUBSIDIARY	PACKING	MARINE
		CLASS	HAZARDS	GROUP	POLLUTANT /
					LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods	

U.S. DOT - RAIL

Not dangerous goods	

U.S. DOT - INLAND WATERWAYS

Not dangerous goods	

TRANSPORT CANADA - ROAD

Not dangerous goods	

TRANSPORT CANADA - RAIL

Not dangerous goods

TRANSPORT CANADA - INLAND WATERWAYS

Not dangerous goods	

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods	

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goo	ds

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods	

ASHLAND	Page: 11
SAFETY DATA SHEET	Revision Date: 05/21/2015
	Print Date: 6/30/2015
	SDS Number: 000000204611
Valvoline™ ULTRAMAX TRANS & DRIVE TRAIN TO-4M	Version: 1.0
786016	

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

	Not dangerous goods	

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards	: Acute Health Hazard	
SARA 311/312 Hazards	: Acute Healt	n Hazard

Chronic Health Hazard

SARA 313 Component(s)

Zinc 11059-65-7 2.22 %

bis[bis(tetrapropylenephen

yl)] bis(hydrogen dithiophosphate)

Pennsylvania Right To Know

HYDROTREATED HEAVY PARAFFINIC 64742-54-7 50.00 - 70.00 %

BASE OIL

HEAVY PARAFFINIC DISTILLATE 64742-54-7 20.00 - 30.00 %

VISCOSITY MODIFIER Not Assigned 10.00 - 20.00 %

LUBRICANT ADDITIVE Not Assigned 1.00 - 5.00 %

New Jersey Right To Know

HYDROTREATED HEAVY PARAFFINIC 64742-54-7 50.00 - 70.00 %

BASE OIL

HEAVY PARAFFINIC DISTILLATE 64742-54-7 20.00 - 30.00 %

VISCOSITY MODIFIER Not Assigned 10.00 - 20.00 %

LUBRICANT ADDITIVE Not Assigned 1.00 - 5.00 %

Mineral Oil Not Assigned 1.00 - 5.00 %

Zinc bis[bis(tetrapropylenephenyl)] 11059-65-7 1.00 - 5.00 %

bis(hydrogen dithiophosphate)

ASHLAND	Page: 12
SAFETY DATA SHEET	Revision Date: 05/21/2015
	Print Date: 6/30/2015
	SDS Number: 000000204611
Valvoline™ ULTRAMAX TRANS & DRIVE TRAIN TO-4M	Version: 1.0
786016	

California Prop 65 Proposition 65 warnings are not required for this product

based on the results of a risk assessment.

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL.

AUSTR : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECL : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 05/21/2015



NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements referred to under sections 2 and 3.

ASHLAND	Page: 13
SAFETY DATA SHEET	Revision Date: 05/21/2015
	Print Date: 6/30/2015
	SDS Number: 000000204611
Valvoline™ ULTRAMAX TRANS & DRIVE TRAIN TO-4M	Version: 1.0
786016	

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H361	Suspected of damaging fertility or the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Sources of key data used to compile the Safety Data Sheet Ashland internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH: American Conference of Industrial Hygienists

BEI: Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx: Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic

PPE: Personal Protective Equipment STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV: Threshold Limit Value TWA: Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

ASHLAND	Page: 14
SAFETY DATA SHEET	Revision Date: 05/21/2015
	Print Date: 6/30/2015
	SDS Number: 000000204611
Valvoline™ ULTRAMAX TRANS & DRIVE TRAIN TO-4M	Version: 1.0
786016	

WEL: Workplace Exposure Level

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

DOT : Department of Transportation

FIFRA: Federal Insecticide, Fungicide, and Rodenticide Act HMIRC: Hazardous Materials Information Review Commission

HMIS: Hazardous Materials Identification System

NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety and Health Administration PMRA: Health Canada Pest Management Regulatory Agency

RTK: Right to Know

WHMIS: Workplace Hazardous Materials Information System