



## Castrol 2T

Durable Protection

### Description

Castrol 2T is modern 2-stroke oil designed to give good all round performance in most 2-stroke motorcycles and other small engine applications. Its low ash formula will help to protect against pre-ignition and provide good engine lubrication and cleanliness to maintain good compression and reliable engine startability throughout its life.

### Application

Castrol 2T is suitable for use in most 2-stroke motorcycle and scooter engines which require good quality engine oil, where API TC and JASO FC specifications are requested. It is designed for both oil injection and pre-mix lubrication, as per manufacturers' instructions, up to a fuel/oil ratio of 50:1.

### Advantages

- Modern 2-stroke motorcycle engine oil.
- Good overall protection against deposits.

## Typical Characteristics

Name	Method	Units	Typical
Density @ 15C, Relative	ASTM D4052	g/ml	0.8737
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	8.3
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	320
Flash Point, PMCC	ASTM D93	°C	119
Pour Point	ASTM D97	°C	-15

## Product Performance Claims

API TC  
JASO FC

## Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol 2T  
16 Oct 2014  
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be referred to for appropriate information regarding storage, safe handling, and disposal of the product. Castrol India Limited shall not be responsible or liable for any damage or injury resulting from abnormal use of the product, from any failure to adhere to recommendations, from any failure to adhere to information regarding storage, safe handling, and disposal of the product or from hazards inherent in the nature of the product. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol India Ltd, Technopolis Knowledge Park, PO Box. 19411, 1st Floor, Mahakali Caves Road, Mumbai - 400093, India  
Technical Advice Line: Customer Service - 1800 209 8100 (Tata Indicom), Phone: 022-6783 9800  
Customer Service: [www.castrol.co.in](http://www.castrol.co.in) Email: [customercare.india@castrol.com](mailto:customercare.india@castrol.com)