



Product Data Sheet

Castrol Activ X-tra 20W-50

Extreme Heat Protection

Description

Castrol Activ X-tra is a modern engine oil formulated with Heat Protection Molecules which ensure your bike engines is protected from harmful high temperature deposits in all driving conditions.

Application

Castrol Activ X-tra is suitable for all motorcycle engine where API SG and JASO MA-2 and MA are recommended.

Advantages

- Gives superior protection from heat.
- Reduces oil thickening.
- Helps keep engine components clean.

Typical Characteristics

Name	Method	Units	Typical
Density @ 15C, Relative	ASTM D4052	g/ml	0.878
Appearance	Visual	-	Clear & Bright
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	19.0
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	167
Viscosity Index	ASTM D2270	None	128
Viscosity, CCS -20C (15W)	ASTM D5293	mPa.s (cP)	6700
Flash Point, PMCC	ASTM D93	°C	210
Total Base Number, TBN	ASTM D2896	mg KOH/g	8.1

Product Performance Claims

API SL
JASO MA2

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Activ X-tra 20W-50

09 Feb 2015

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be referred to for appropriate information regarding storage, safe handling, and disposal of the product. Castrol India Limited shall not be responsible or liable for any damage or injury resulting from abnormal use of the product, from any failure to adhere to recommendations, from any failure to adhere to information regarding storage, safe handling, and disposal of the product or from hazards inherent in the nature of the product. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol India Ltd, Technopolis Knowledge Park, PO Box. 19411, 1st Floor, Mahakali Caves Road, Mumbai - 4000093, India

Technical Advice Line: Customer Service - 1800 209 8100 (Tata Indicom), Phone: 022-6783 9800

Customer Service: www.castrol.co.in Email: customercare.india@castrol.com