



Hysol™ 6519

High performance semi-synthetic metalworking fluid

Description

Castrol Hysol™ 6519 (previously called Clearedge™ 6519) is high performance semi-synthetic metalworking fluid which is chlorine and formaldehyde releasing agent free. It contains a unique additive package that works in synergy to enhance machining performance and surface finish, provide excellent product stability, improve bio-resistance properties and lower the overall operations costs.

Hysol 6519 is suitable for large central systems and single sump machines.

Application

Hysol 6519 is especially designed for grinding and machining of aluminium alloys and low-medium alloyed steel.

ü ü suggested core application ü possible application, please consult Castrol representative prior to use

	Cast Iron	Low-medium alloyed steel	High alloyed - stainless steel	Aluminium alloys	Magnesium	Yellow metals
Grinding	ü ü	ü ü	ü	ü		
Miling, Turning (general machining)	ü ü	ü ü	ü	ü		
Drilling	ü ü	ü ü	ü	ü		
Reaming, Tapping	ü	ü				
Broaching						

Advantages

- Chlorine and nitrite free to fulfill your local legislation, waste treatment and environmental requirements
- Resists fungal and bacterial attack to extend fluid life and reduce maintenance and machine downtime
- Low foam in recommended water conditions
- Excellent wetting properties reduce coolant drag out and deliver clean machine tools and components
- Unique multi-functional product for multi-metal operations results in product consolidation

Typical Characteristics

Name	Method	Units	Hysol 6519
<i>Concentrate</i>			
Appearance	Visual	-	Yellow
Mineral Oil content	Calculated	Wt%	29
<i>Emulsion</i>			
Appearance	Visual		Translucent
pH (5%)	ASTM E70-97 DIN 51361		9.3
Refractometer Factor			1.4

Subject to usual manufacturing tolerances.

Subject to usual manufacturing tolerances.

Recommended Concentrations

Grinding	4-5%
General Machining	4-8%
Water Range	100-400 pm CaCO ₃

Storage

To avoid product deterioration always keep the container/drum tightly sealed. Store the product in a cool, dry place away from direct sunlight. Prevent exposure to frost and avoid water ingress. For optimum product stability, it is preferable to store the product indoors between 5°C and 45 °C / 41°F and 113°F.

For more details, please refer the product safety data sheet.

This product was previously called Clearegde 6519. The name changed in 2015

Hysol™ 6519

27 Feb 2015

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be referred to for appropriate information regarding storage, safe handling, and disposal of the product. Castrol India Limited shall not be responsible or liable for any damage or injury resulting from abnormal use of the product, from any failure to adhere to recommendations, from any failure to adhere to information regarding storage, safe handling, and disposal of the product or from hazards inherent in the nature of the product. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol India Limited, Industrial Lubricants & Services Rayala Towers , II Tower , V Floor 781-785 , Anna Salai , Chennai – 600 002

Tel: +91 44 42198899 / 823 Fax: +91 44 28416305 Toll Free: 1800 - 425 - 4588 (BSNL) Help Line: 044-42198885 Email: CustomerService.India@castrol.com
www.castrol.com/industrial