



Product Data

Castrol LCG 2 Grease™ Lithium Complex Grease

Description

Castrol LCG 2 is a premium quality grease manufactured from lithium complex soap, highly refined mineral oils and fortified with extreme pressure and antiwear additives. The superiority of Castrol LCG 2 over conventional greases can be exhibited by its high drop point of over 260 °C, excellent roll stability, superior water washout resistance, low coefficient of friction, high load carrying ability, good adhesion property and resistance to oil separation under pressure. This makes Castrol LCG 2 single grease suitable for multitude of applications.

Application

Castrol LCG 2 grease offers effective lubrication up to a working temperature range of 160° C. and is suitable for lubrication of all types of bearings encountering higher than average temperature, high speed, needing centralised lubrication and exposed to shock, overloading and contamination. Castrol LCG 2 grease provides trouble free, cost effective long life lubrication in heavy duty applications encountered in glass, steel, cement, metallurgy & mining industry such as electric motors, hot air fins, vibrating shafts, bucket pins, excavators, HEMM etc. It also finds application in disc brakes in the automotive industry.

Advantages

Product Features	Operational Advantages	Customer Benefits
High drop point	Excellent lubrication at peak temperatures	Lower bearing failures
High structure stability	Reduced grease thinning under vibrating conditions	Increased re-lubrication intervals / Long service life
Effective Lubrication in wet condition	Minimal washout of grease in wet conditions	Extended bearing life
Excellent lubrication under heavy loads and low speed	Lower bearing temperatures and bearing failure due to low coefficient of friction	Higher bearing life and lower power consumption.

Castrol LCG 2 Grease
11.11.2006, Version Number 1.0
"Castrol LCG 2 Grease" and Castrol are trademarks of Castrol Limited, used under licence.

All reasonable care has been taken to ensure that the information included in this publication is accurate as of the date of printing. However, such information may nevertheless be affected by changes in the blend formulation occurring subsequent to the date of printing. Material Safety Data Sheets are available for all Castrol India Limited products. MSDS must be consulted for appropriate information regarding storage, safe handling and disposal of a product

Castrol India Limited, Industrial Lubricants & Services, Rayala Towers, II Tower, V Floor, 781-785, Anna Salai, Chennai – 600 002.
Tel: +91 44 42198899 Fax: +91 44 28416305 Toll Free: 1800 - 425 - 4588 (BSNL) Help Line: 044-39019019
Email:customer.service@castrol.com



Product Data

Characteristics

Characteristics	Typical Value
Appearance	Smooth Grease
Soap Type	Lithium Complex
NLGI Consistency NO.	2
Pene. Worked 60 X @ 25 °C	280
Drop Point, °C	270
4 Ball EP Test, Kg	320
4 Ball Wear Scar Dia.	0.5
Rust Protection, EMCOR, Rating	"0"
Corr. Prev. properties Grease	Passes

These are typical figures and do not constitute a specification.

Castrol LCG 2 Grease
11.11.2006, Version Number 1.0
"Castrol LCG 2 Grease" and Castrol are trademarks of Castrol Limited, used under licence.

All reasonable care has been taken to ensure that the information included in this publication is accurate as of the date of printing. However, such information may nevertheless be affected by changes in the blend formulation occurring subsequent to the date of printing. Material Safety Data Sheets are available for all Castrol India Limited products. MSDS must be consulted for appropriate information regarding storage, safe handling and disposal of a product

Castrol India Limited, Industrial Lubricants & Services, Rayala Towers, II Tower, V Floor, 781-785, Anna Salai, Chennai – 600 002.
Tel: +91 44 42198899 Fax: +91 44 28416305 Toll Free: 1800 - 425 - 4588 (BSNL) Help Line: 044-39019019
Email:customer.service@castrol.com