



Product Data

Castrol Magna Slideway GC 32™

Slide Way Lubricant

Application

Castrol Magna slideway oils are a range of lubricants based upon highly refined mineral oils, which incorporate tackiness and lubricity additives to give smooth slideway movement under heavy loads. The range incorporates grades to suit most of the machines, details of their particular applications being given below.

Magna GC 32 - is a light viscosity slideway lubricant designed for machine tools fitted with combined hydraulic and slideway lubrication systems.

Characteristics

Characteristics	Typical Value
Appearance	Bright Clear Liquid
Rel Density @ 29.5 °C	0.870
Kinematic viscosity @ 40 °C, cSt	32
Kinematic Viscosity, cSt, @ 100°C.	5.3
VI	96
Flash Point, COC, °C	218
Pour Point °C	-9
Rust Prev. Charac	Pass

These are typical figures and do not constitute a specification.

Castrol Magna Slideway GC 32
11.11.2006, Version Number 1.0
"Castrol Magna Slideway GC 32" and Castrol are trademarks of Castrol Limited, used under licence.

All reasonable care has been taken to ensure that the information included in this publication is accurate as of the date of printing. However, such information may nevertheless be affected by changes in the blend formulation occurring subsequent to the date of printing. Material Safety Data Sheets are available for all Castrol India Limited products. MSDS must be consulted for appropriate information regarding storage, safe handling and disposal of a product

Castrol India Limited, Industrial Lubricant & Services, Rayala Towers, II Tower, V Floor, 781-785, Anna Salai, Chennai – 600 002.
Tel: +91 44 42198899 Fax: +91 44 28416305 Toll Free: 1800 - 425 - 4588 (BSNL) Help Line: 044-39019019
Email:customer.service@castrol.com