



## Product Data

### Castrol Rustilo 630™ Neat Corrosion Preventive oil

#### Description

*These are specially selected lubricating oils, containing soluble anti-rust inhibitors, to offer high degree of corrosion prevention. These grades serve as lubricants as well as temporary protectives. Rustilo 630 can be applied by dipping, spraying, roller coating, flowcoating, flushing or circulation, but the application surface must be cleaned and dried. The protective film of these grades has lubricating properties and hence is not necessary to remove. However, if desired, the film can be removed by wiping.*

#### Application

*This grade is of a viscosity similar to that of spindle oil. It offers a thin lubricating film. It is used for protection of steel sheets, precision and drawn tubes, exposed gearings, shaftings, conveyors, etc.*

#### Advantages

Product Feature	Operational Advantage	Customer Benefits
Oily film	Easy to apply and also to remove	Easy usability
Low Viscosity	Good finishing characteristics	Internal protection of gearboxes and engines.

Castrol Rustilo 630  
02.11.2006, Version Number 1.0  
"Castrol Rustilo 630" and Castrol are trademarks of Castrol Limited, used under licence.

All reasonable care has been taken to ensure that the information included in this publication is accurate as of the date of printing. However, such information may nevertheless be affected by changes in the blend formulation occurring subsequent to the date of printing. Material Safety Data Sheets are available for all Castrol India Limited products. MSDS must be consulted for appropriate information regarding storage, safe handling and disposal of a product

Castrol India Limited, Industrial Lubricants & Services, Rayala Towers, II Tower, V Floor, 781-785, Anna Salai, Chennai – 600 002.  
Tel: +91 44 42198899 Fax: +91 44 28416305 Toll Free: 1800 - 425 - 4588 (BSNL) Help Line: 044-39019019  
Email:customer.service@castrol.com



## Product Data

### Characteristics

Characteristics	Typical Value
Appearance	Yellow fluid
Specific gravity @ 30°C	0.880
Kin. Viscosity @ 40°C	33
Flash point °C PMCC	180
Coverage (Sq. mt./ltr.)	90-100
Film Thickness, Micron	7-8
Humidity Cabinet, Days	12 +
Salt Spray, Hrs	7 +
Protection - Indoors	4 months
- Outdoors	1 month

*The above data is typical and does not constitute a specification*

Castrol Rustilo 630  
02.11.2006, Version Number 1.0  
"Castrol Rustilo 630" and Castrol are trademarks of Castrol Limited, used under licence.

All reasonable care has been taken to ensure that the information included in this publication is accurate as of the date of printing. However, such information may nevertheless be affected by changes in the blend formulation occurring subsequent to the date of printing. Material Safety Data Sheets are available for all Castrol India Limited products. MSDS must be consulted for appropriate information regarding storage, safe handling and disposal of a product

Castrol India Limited, Industrial Lubricants & Services, Rayala Towers, II Tower, V Floor, 781-785, Anna Salai, Chennai – 600 002.  
Tel: +91 44 42198899 Fax: +91 44 28416305 Toll Free: 1800 - 425 - 4588 (BSNL) Help Line: 044-39019019  
Email:customer.service@castrol.com