



Product Data

Castrol Rustilo DW 901™ De-Watering Corrosion Preventive

Description

These are soft film, solvent deposited, water displacing type, corrosion preventives. These fluids can be applied directly to water wet metal surfaces, where they displace water, leaving a protective film. All these fluids have excellent spreading and they can be applied either by dipping or by spraying. The protective films of all these grades can be removed by wiping off with rags/waste soaked in kerosene/mineral turpentine or by alkaline degreasants or solvent degreasing methods. Rustilo DW 901 comply to IS: 1154 specifications.

Application

This grade is intended for severe conditions and leaves a greasy film. The film is resistant to handling and gives excellent protection. It can be used for protection during storage of valuable machine tools and as a final protective for tools and machined components in factory stores or shops.

These are water displacing, thin film type corrosion preventives.

Rustilo DW 901 leaves a greasy film and is recommended for final protection of machine tools and components.

Characteristics

Characteristics	Typical Value
Appearance	Amber, clear fluids
Specific gravity@30°C	0.828
Flash point °C	40
Protection - Indoors	12 months
- Outdoors	3 months
Coverage (sq.mt. /ltr)	25-35
Film thickness (microns)	5
Water displacement test as per IS: 1154	Passes

These are typical figures and do not constitute a specification.

Castrol Rustilo DW 901
02.11.2006, Version Number 1.0
"Castrol Rustilo DW 901" and Castrol are trademarks of Castrol Limited, used under licence.

All reasonable care has been taken to ensure that the information included in this publication is accurate as of the date of printing. However, such information may nevertheless be affected by changes in the blend formulation occurring subsequent to the date of printing. Material Safety Data Sheets are available for all Castrol India Limited products. MSDS must be consulted for appropriate information regarding storage, safe handling and disposal of a product

Castrol India Limited, Industrial Lubricants & Services, Rayala Towers, II Tower, V Floor, 781-785, Anna Salai, Chennai – 600 002.
Tel: +91 44 42198899 Fax: +91 44 28416305 Toll Free: 1800 - 425 - 4588 (BSNL) Help Line: 044-39019019
Email:customer.service@castrol.com