



Product Data

Castrol Rustilo DW 950™

De-watering fluid

Description

These are soft film, solvent deposited, water displacing type, corrosion preventives. These fluids can be applied directly to water wet metal surfaces, where they displace water, leaving a protective film. All these fluids have excellent spreading and they can be applied either by dipping or by spraying. The protective films of all these grades can be removed by wiping off with rags/waste soaked in kerosene/mineral turpentine or by alkaline degreasants or solvent degreasing methods.

Application

This grade offers a dry surface on the component and is ideally suited for use on electroplated / anodised components. It can also be used on steel components, which are to be subsequently painted or treated with a rust preventive, which does not have dewatering properties.

These are water displacing, thin film type corrosion preventives.

Rustilo DW 950 offers dry surface on components and is ideally suited for use on electroplated / anodised components.

Characteristics

Characteristics	Typical Value
Appearance	Water white clear fluid
Specific gravity@30°C	0.780
Flash point °C	40
Protection – Indoors	-
- Outdoors	-
Coverage (sq.mt./ltr)	-
Film thickness (microns)	-
Water displacement test as per IS: 1154	Passes

These are typical figures and do not constitute a specification.

Castrol Rustilo DW 950
03.11.2006, Version Number 1.0
"Castrol Rustilo DW 950" and Castrol are trademarks of Castrol Limited, used under licence.

All reasonable care has been taken to ensure that the information included in this publication is accurate as of the date of printing. However, such information may nevertheless be affected by changes in the blend formulation occurring subsequent to the date of printing. Material Safety Data Sheets are available for all Castrol India Limited products. MSDS must be consulted for appropriate information regarding storage, safe handling and disposal of a product

Castrol India Limited, Industrial Lubricant & Services, Rayala Towers, II Tower, V Floor, 781-785, Anna Salai, Chennai – 600 002.
Tel: +91 44 42198899 Fax: +91 44 28416305 Toll Free: 1800 - 425 - 4588 (BSNL) Help Line: 044-39019019
Email:customer.service@castrol.com

www.castrol.com/industrial