



Gulf Formula PCX

Catalyst Compatible Synthetic Passenger Car Motor Oil

Product Description

Gulf Formula PCX is the most advanced high performance passenger car motor oil formulated from synthetic base stocks and state-of-the-art additive technology to provide fuel savings and to prolong the life & maintain the efficiency of emission reducing systems. It is fully compatible with Diesel Particulate Filter (DPF) and Gasoline Three Way Catalyst (TWC). It is specially developed to exceed the service fill requirements of PSA Peugeot Citroën and other OEMs requiring ACEA C2 type of oils.

Features & Benefits

- Low SAPS (Sulphated Ash Phosphorus Sulphur) oil formulation prolongs the life and maintains the efficiency of DPF and TWC.
- Outstanding thermo-oxidative stability resists oil degradation and thus facilitates extended oil change intervals
- Active cleaning agents reduce deposits & sludge and keeps engine clean.
- Enhanced frictional properties provide improved fuel economy (ACEA C2) compared to mineral engine oils.
- Excellent antiwear technology leads to superior wear protection
- Exceptional Stay-in-Grade performance ensures reliable lubrication even at higher loads & operating temperatures
- Outstanding low temperature fluidity aids quick cold start and provides wear protection at start-up

Applications

- Latest generation passenger cars, SUV's and light vans of Peugeot and Citroën requiring oils meeting PSA Peugeot Citroën B71 2290 specification
- Modern high performance gasoline and diesel engines in passenger cars and light duty vehicles fitted with DPF and TWC requiring catalyst compatible fuel economy oils meeting ACEA C2 specifications.
- North American and Japanese passenger cars requiring oils meeting API SM/ CF.
- These oils may be unsuitable for use in some engines (consult owner manual/ handbook).

Specifications, Approvals & Typical Properties

Specifications		5W-30
ACEA C2		X
API SM/ CF		X
PSA Peugeot Citroën B71 2290		X
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Viscosity @ 100 °C, cSt	D 445	10.5
Viscosity Index	D 2270	162
Flash Point, °C	D 92	226
Pour Point, °C	D 97	-39
Density @ 15°C, Kg/l	D 1298	0.855
Sulfated Ash, % wt	D 874	0.78
Phosphorus, % wt	D 4047 (ICP)	0.077

May 2015

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. The above information is based on past history of the grade only and must not be construed as a guarantee of performance. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The Material Safety Data Sheet for this product is available from your nearest Gulf Distributor.

Gulf Oil International

The information contained herein is believed to be correct at time of publication. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

www.gulfoilltd.com