



Gulf Power Trac 2T

Semi-Synthetic, Low Smoke 2-Stroke Motorcycle Oil

Product Description

Gulf Power Trac 2T is a superior quality semi-synthetic low smoke lubricant designed for use in 2-stroke air cooled gasoline engines. It is formulated from high quality base stocks, synthetic base fluids and special additives to provide excellent engine protection, cleanliness and low smoke in 2-stroke motorcycle/ scooter engines operating in different conditions. The product meets the international specifications of JASO FC & API TC and the requirements of leading global 2-stroke motorcycle/ scooter manufacturers.

Features & Benefits

- Excellent lubricity and antiwear properties protect against piston scuffing and premature wear of engine components
- Unique formulation provides excellent control against engine deposits, exhaust system blocking and extended engine life without power loss
- Low ash additive technology prevents pre-ignition and spark plug fouling
- Synthetic base fluids used in this oil reduces visible exhaust smoke
- Easy miscibility with gasoline ensures stable homogeneous mixture even at low ambient temperatures

Applications

- Recommended for high-powered 2-stroke motorcycles/ scooters under all types of road and traffic conditions
- Suitable for both oil-injection and premix lubrication systems; follow manufacturer's recommendations for oil to fuel ratio
- Also recommended for high performance 2-stroke engines in all terrain vehicles, gardening equipment and other variety of applications requiring oil of this quality

Specifications, Approvals & Typical Properties

| Meets the following Specifications | | |
|------------------------------------|-------------|----------------|
| API TC | | |
| Has the following On File Status | | |
| JASO FC | | |
| Typical Properties | | |
| Test Parameters | ASTM Method | Typical Values |
| Viscosity @ 100 °C, cSt | D 445 | 7.80 |
| Flash Point, °C | D 93 | 89 |
| Pour Point, °C | D 97 | -3 |
| TBN, mg KOH/g | D 2896 | 0.80 |
| Density @ 15°C, Kg/l | D 1298 | 0.857 |
| Sulphated Ash, %wt | D 874 | 0.09 |

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. The above information is based on past history of the grade only and must not be construed as a guarantee of performance. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The Material Safety Data Sheet for this product is available from your nearest Gulf Distributor.

Gulf Oil International

The information contained herein is believed to be correct at time of publication. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

www.gulfoilltd.com