



Gulf Pride 4T 4-Stroke Motorcycle Oil

Product Description

Gulf Pride 4T is a high quality 4-stroke gasoline engine oil developed specifically to meet the special requirements of air cooled 4-stroke motorcycles. It is blended from highly refined base oils and performance additives to provide protection to engine, gear box and wet clutch used in 4-stroke motorcycles. The product exceeds the international specifications of API SG and JASO MA for 4-stroke motorcycle oils and the requirements of leading global 4-stroke motorcycle manufacturers. It is available in five different viscometrics, viz SAE 10W-40, SAE 15W-40, SAE 15W-50, SAE 20W-40 and SAE 20W-50.

Features & Benefits

- Excellent antiwear properties protect vital engine and gear components leading to reduced maintenance costs
- Good thermo-oxidative stability prevents harmful deposit formation and controls oil thickening facilitating extended engine and oil life
- Controlled frictional properties eliminate clutch slippage and improves drivability
- Better detergency/ dispersancy keeps engine cleaner and reduces maintenance costs
- Effective rust and corrosion inhibition property ensures longer life of critical engine components

Applications

- Recommended for air cooled 4-stroke motorcycle engines where an API SG and JASO MA quality oil is required
- Also suitable for small 4-stroke gasoline engines used in portable generators, pumps, garden machinery and other applications

Specifications, Approvals & Typical Properties

Meets the following Specifications		10W-40	15W-40	15W-50	20W-40	20W-50
API SG, JASO MA		X	X	X	X	X
Has the following On File Status						
JASO MA					X	X
Typical Properties						
Test Parameters	ASTM Method	Typical Values				
Viscosity @ 100 °C, cSt	D 445	14.6	14.2	18.3	14.4	18.6
Viscosity Index	D 2270	160	137	147	119	126
Flash Point, °C	D 92	234	232	236	254	256
Pour Point, °C	D 97	-33	-24	-24	-24	-24
TBN, mg KOH/g	D 2896	7.1	7.1	7.1	7.1	7.1
Density @ 15°C, Kg/l	D 1298	0.877	0.871	0.869	0.895	0.894
Sulphated Ash, %wt	D 874	0.85	0.85	0.85	0.85	0.85

August 2012

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. The above information is based on past history of the grade only and must not be construed as a guarantee of performance. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The Material Safety Data Sheet for this product is available from your nearest Gulf Distributor.

Gulf Oil International

The information contained herein is believed to be correct at time of publication. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

www.gulfoilttd.com