



Gulf Pride 4T Plus

Premium 4-Stroke Motorcycle Oil

Product Description

Gulf Pride 4T Plus is a premium quality 4-stroke gasoline engine oil developed specifically to meet the special requirements of the latest high performance air cooled 4-stroke motorcycles. It is blended from superior quality high viscosity index base oils and specially selected performance additives to provide excellent protection for engine, gearbox and wet clutch used in 4-stroke motorcycles. SAE 5W-30, SAE 10W-30 & SAE 10W-40 are semi-synthetic. It provides high degree of reliability even under severe operating conditions. This oil exceeds the international specification JASO MA for 4-stroke motorcycle oils and the requirements of leading global 4-stroke motorcycle manufacturers.

Features & Benefits

- Outstanding thermo-oxidative stability minimises high temperature deposit formation and controls oil thickening facilitating extended engine and oil life
- Exceptional antiwear properties protect vital engine and gear components leading to reduced maintenance costs
- Optimised frictional properties eliminate wet clutch slippage leading to increased power / fuel economy and improved drivability
- Unique combination of detergents and dispersants provide excellent control on piston deposits leading to faster heat dissipation and longer engine life
- Excellent shear stability maintains viscosity under high temperature-high shear environment and provides improved wear protection
- Exceptional low volatility characteristics reduce oil consumption and hydrocarbon pollution
- Effective rust and corrosion inhibition property ensures longer life of critical engine components

Applications

- Recommended for new generation 4-stroke gasoline engines in high performance motorcycles of all leading global manufacturers

Specifications, Approvals & Typical Properties

Meets the following Specifications		5W-30	10W-30	10W-40	20W-40	20W-50
API SL		X		X	X	X
JASO MA		X		X	X	X
JASO MA2			X			
Typical Properties						
Test Parameters	ASTM Method	Typical Values				
Viscosity @ 100 °C, cSt	D 445	9.5	11.0	14.6	14.50	18.7
Viscosity Index	D 2270	153	145	154	112	127
Flash Point, °C	D 92	228	234	234	240	243
Pour Point, °C	D 97	-36	-33	-36	-24	-24
TBN, mg KOH/g	D 2896	7.0	9.3	7.0	6.50	8.1
Density @ 15°C, Kg/l	D 1298	0.868	0.871	0.878	0.883	0.894
Sulphated Ash, %wt	D 874	0.83	1.0	0.83	0.91	1.13

May 2015

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. The above information is based on past history of the grade only and must not be construed as a guarantee of performance. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The Material Safety Data Sheet for this product is available from your nearest Gulf Distributor.

Gulf Oil International

The information contained herein is believed to be correct at time of publication. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

www.gulfoilltd.com