



Gulf Pride 4T Special

High Performance 4-Stroke Motorcycle Oil

Product Description

Gulf Pride 4T Special is a high-performance 4-stroke engine oil developed specifically to meet the special requirements of high-speed air cooled 4-stroke motorcycles. It is blended from highly refined base oils and specially selected performance additives to provide enduring protection for engine, gearbox and wet clutch used in 4-stroke motorcycles. This oil meets/exceeds the international specifications of API SJ and JASO MA for 4-stroke motorcycle oils and the requirements of leading global 4-stroke motorcycle manufacturers. It is available in three different viscometrics viz. 15W-40, 20W-40 and 20W-50.

Features & Benefits

- Improved thermo-oxidative stability minimises high temperature deposit formation and controls oil thickening facilitating extended engine and oil life.
- Superior detergents and dispersants help keep engine parts clean thereby prolonging equipment life.
- Excellent anti-wear properties protect vital engine and gear components leading to reduced maintenance costs.
- Controlled frictional properties ensure smooth wet clutch operation leading to smoother operation and improved drivability.
- Effective rust and corrosion inhibition property ensures longer life of critical engine components.

Applications

- Recommended for current generation 4-stroke gasoline engines in high performance motorcycles of all leading global manufacturers.
- Also suitable for small 4-stroke gasoline engines used in portable generators, pumps, garden machinery and other applications where such type of oils are recommended.

Specifications, Approvals & Typical properties

Meets the following specifications		15W-40	20W-40	20W-50
API SJ		X	X	X
JASO MA		X	X	X
Has the following On-File registration				
JASO MA		X	X	X
Typical Properties				
Test Parameters	ASTM Method	Typical Values		
Viscosity @ 100 °C, cSt	D 445	14.2	13.1	19.6
Viscosity Index	D 2270	137	110	128
Flash Point, °C	D 92	238	249	256
Pour Point, °C	D 97	-27	-24	-24
TBN, mg KOH/g	D 2896	6.8	7.0	7.0
Density @ 15°C, Kg/l	D 1298	0.8881	0.8958	0.8932
Sulphated Ash, %wt	D 874	0.95	0.9	0.95

December 2014

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. The above information is based on past history of the grade only and must not be construed as a guarantee of performance. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The Material Safety Data Sheet for this product is available from your nearest Gulf Distributor.

Gulf Oil International

The information contained herein is believed to be correct at time of publication. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

www.gulfoilltd.com