



Gulf Snowmobile 2T

2-Stroke Snowmobile Oil

Product Description

Gulf Snowmobile 2T is a high quality lubricant suitable for use in air cooled 2-stroke gasoline engines deployed in snowmobiles. It is blended from high quality base stocks and fortified with carefully selected additives to provide engine protection and cleanliness in 2-stroke engines. The product meets the international specifications of API TC and JASO FB.

Features & Benefits

- Excellent lubricity protects against piston scuffing and premature wear of engine components
- Proven additive technology controls engine and exhaust system deposits
- Low ash formula prevents pre-ignition and spark plug fouling
- Excellent low temperature properties making it suitable for extreme cold weather conditions
- Easy miscibility with gasoline ensures stable homogeneous mixture even at low ambient temperatures

Applications

- Recommended for 2-stroke snowmobiles requiring API TC and JASO FB quality oil
- Suitable for both oil-injection and premix lubrication systems; follow manufacturer's recommendation for oil to fuel ratio
- Also recommended for 2-stroke engines in other applications like motorcycles and scooters requiring this quality oil

Specifications & Typical Properties

Meets the following Specifications		
API TC		
JASO FB		
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Viscosity @ 100 °C, cSt	D 445	9.15
Flash Point, °C	D 93	78
Pour Point, °C	D 97	-36
TBN, mg KOH/g	D 2896	0.80
Density @ 15°C, Kg/l	D 1298	0.875
Sulphated Ash, %wt	D 874	0.09

October 2009

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. The above information is based on past history of the grade only and must not be construed as a guarantee of performance. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The Material Safety Data Sheet for this product is available from your nearest Gulf Distributor.

Gulf Oil International

The information contained herein is believed to be correct at time of publication. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

www.gulfoilltd.com