

Gulf Super Duty HT Commercial Vehicle Engine Oil

Product Description

Gulf Super Duty HT is a performance monograde diesel engine oil developed for a wide range of diesel engines operating under severe conditions. It is formulated using special base stocks and selected additives to impart high reserve alkalinity which makes it ideally suited for engines running on high sulphur high speed diesel. It is suitable for use in a wide range of applications where such monograde lubricant is recommended.

Features & Benefits

- High TBN reserve helps in countering the harmful effects of acids generated during use of high sulphur motor fuels and protects vital engine parts against corrosion and wear
- Improved detergency helps reduce deposits and keeps engines cleaner
- Better thermo-oxidative stability protects against sludge build-up, deposits & oil degradation and controls oil thickening
- Effective anti wear properties protect engine components against wear to offer extended engine life and reduced maintenance costs

Applications

- Turbocharged and naturally aspirated diesel engines of all leading engine manufacturers operating on high sulphur high speed diesel
- On-highway applications including light and heavy duty applications
- Heavy-duty diesel engines used in mining, construction, agriculture and other off-highway applications

Specifications & Typical Properties

Meets the following specifications		40	50	60
API CF		Х	Х	Х
Typical Properties				
Test Parameters	ASTM Method	Typical Values		
Viscosity at 100 °C, cSt	D 445	14.00	18.50	24.22
Viscosity Index	D 2270	95	95	99
Flash Point, °C	D 92	240	250	260
Pour Point, °C	D 97	-12	-9	-9
TBN, mg KOH/g	D 2896	12.00	12.00	12.00
Density @ 15°C, Kg/l	D 1298	0.893	0.899	0.910
Sulphated Ash, %wt	D 874	1.70	1.70	1.70

May 2013