



PRODUCT DATA SHEET

GulfSea Power MX 15W-40

Multigrade Marine Oil specially formulated for highly turbo-charged diesel engines and particularly suitable for life boat engines, emergency diesel engine generators, fire pumps (IMO international safety rules) in extreme weather conditions, etc.

Product Description

GulfSea Power MX 15W-40 is an extra high performance diesel engine oil that provides superior performance and long service potential in high output, high-speed turbocharged diesel engines operating under severe conditions. It is blended from highly refined base stocks and carefully selected additives to provide excellent control of oil thickening; high temperature deposits and inhibits oxidation and corrosion. It meets the requirements of major European heavy-duty diesel engine manufacturers.

Features & Benefits

- Excellent thermo-oxidative stability controls deposits & viscosity increase.
- Exceptional anti wear properties protect critical engine components to extend engine life and reduce maintenance costs.
- Advanced detergency reduces deposits and enhances engine cleanliness to provide extended engine life.
- Better high temperature – high shear stability protects against bore polishing.

Applications

- Turbocharged and naturally aspirated low emission diesel engines of major European & American engine manufacturers.
- On highway light and heavy duty trucking including high speed-high load service and short haul pick-up/delivery van.
- Heavy duty diesel engines used in mining, construction, agriculture and other off highway applications.

Typical Properties

GulfSea Power MX 15W-40		
Meets the following Specifications		
API CH-4		
Mack EO-M		
Cummins 20071, 20072		
Daimler MB 228.3		
MAN M 3275		
Volvo VDS-2		
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Viscosity @ 100 °C, cSt	D 445	14.5
Viscosity Index	D 2270	135
Flash Point, °C	D 92	230
Pour Point, °C	D 97	-27
BN, mg KOH/g	D 2896	9.8
Density @ 15 °C, Kg/l	D 1298	0.89

July 2014