

MAK 4T STALLION

Description

MAK 4T STALLION is premium quality multi grade oil, which is blended with hydro processed group II plus base oil. This oil guards against wear by providing superior oil film strength. Higher viscometrics of this oil provides better lubrication at all operating temperatures & reduces Engine Noise. This oil provides outstanding resistance to oxidation which degrades the oil.

Application

MAK 4T STALLION is recommended for new generation 4 stroke motorcycles.

Benefits

- Exceptional thermal stability: Resist oxidation and high-temperature degradation
- Outstanding wear protection: Help in extending engine and transmission components life
- Enhanced lubrication: Help maintain maximum power and acceleration
- Special frictional properties: Optimized wet-clutch performance
- Higher viscometrics: Better lubrication at all operating temperatures & reduces Engine Noise

Performance Level

- API SL
- JASO MA2

Technical Specifications

Characteristics	ASTM TEST METHOD	MAK 4T STALLION 20W-50
Appearance	-	Clear
Colour, Visual	-	Brown
K.V.@100 deg C, cSt	D-445	18.5
Viscosity Index	D-2270	130
Flash Point(COC), deg C	D-92	235
Pour Point, deg C	D-97	-21
Copper Corrosion@ 100 deg C for 3 Hrs.	D-130	1a
Foaming tendency a) sequence I b) sequence II c) sequence III	D-892	Nil/Nil 10/Nil Nil/Nil

All the mentioned values are typical which may vary from batch to batch.

Storage and Handling

- Indoor Storage is always preferable
- Barrels should be kept horizontally with bunk position at 3 O'clock 9 O'clock position
- Barrels should be kept away from dusty or heated areas.
- During handling any contact with dust must be avoided

Health & Safety

This grade is not hazardous under normal conditions of use. For further guidance Material Safety Data Sheet (MSDS) may be referred.

Advice

For any further advice on applications or otherwise, please contact the nearest Bharat Petroleum territory office or Technical Services department at the address given below.

Bharat Petroleum Corporation Ltd.

Product and Application Development Dept.
 BPCL 'A' Installation, Sewree Fort Road, Sewree (East)
 Mumbai -400015
 E-mail: MAKcustomer care2@bharatpetroleum.in
 Tel No.: 022-24176351