

MAK BOAT XP

Description

High performance diesel engine oil formulated using superior quality base oil and unique additive technology to provide excellent protection under all operating conditions, especially under marine environment thereby reducing maintenance.

Application

- Recommended for naturally aspirated or turbocharged diesel engines
- Recommended for models of Ashok Leyland - 411 & 412 and other OEMs powering all fishing boats and trawlers.

Benefits

- Outstanding oxidation stability : Ensures cleaner engine and extended oil life
- Good wear protection
- Excellent sludge and varnish control : Minimizes engine deposit & reduces maintenance cost
- Being Multi grade oils, these are suitable for use in all seasons

Performance Level

- API CH-4
- MB 228.3

Technical Specifications

Characteristics	ASTM	MAK BOAT XP 15W-40
Appearance	--	Clear & Bright
Colour, Visual Observation		Brown
Density @15°C, gm/ml	D-1298	0.8885
K.V.@100 deg C, cSt	D-445	14.20
Viscosity Index	D-2270	145
Pour Point, °C	D-97	-24
Flash Point, (COC), °C	D-92	232
Copper corrosion @100°C for 3 hrs	D-130	1a

All the mentioned values are typical which may vary from batch to batch

Storage and Handling

- Indoor Storage is always preferable
- Barrels should be kept horizontally with bunk position at 3 O'clock 9 O'clock position
- Barrels should be kept away from dusty or heated areas.
- During handling any contact with dust must be avoided

Health & Safety

This grade is not hazardous under normal conditions of use. For further guidance Material Safety Data Sheet (MSDS) may be referred.

Advice

For any further advice on applications or otherwise, please contact the nearest Bharat Petroleum territory office or Technical Services department at the address given below.

Bharat Petroleum Corporation Ltd.

Product and Application Development Dept.
BPCL 'A' Installation, Sewree Fort Road, Sewree (East)
Mumbai -400015
E-mail: MAKcustomer care2@bharatpetroleum.in
Tel No.: 022-24176351