

MAK GES-LA

Description

MAK GES-LA It is premium quality low ash heavy-duty Gas Engine Oil which are a blend of specially selected High Viscosity Index Base oils and carefully balanced additives.

Application

Recommended for use in highly rated spark ignition stationary Natural Gas engines used for gas gathering/compression, power generation requiring low ash oil

Benefits

These oils provide an excellent oxidation, nitration, deposit and wear control.

- Consists of ash-containing and ash-less detergents – dispersants
- Contains anti – oxidation, anti – wear and anti – corrosion additives
- Good anti – foaming agents

PERFORMANCE LEVEL

- API CF

Technical Specifications

Characteristics	ASTM Test methods	MAK GES LA		
		30	40	15W-40
Appearance	--	Clear & Bright	Clear & Bright	Clear & Bright
Colour, Visual Observation	--	Brown	Brown	Brown
Density @15°C	D1298	0.885	0.891	0.895
K.V at 100° C, cSt	D445	11	14.5	14.5
Viscosity Index	D2270	95	95	132
Flash Point, (COC), °C	D92	226	232	238
Pour Point, °C	D97	-9	-9	-24
Copper corrosion @ 100°C for 3 hrs.	D130	1a	1a	1a

All the mentioned values are typical which may vary from batch to batch.

Storage and Handling

- Indoor Storage is always preferable
- Barrels should be kept horizontally with bung position at 3'O clock 9 'O clock position
- Barrels should be kept away from dusty or heated areas as much as possible

Health and Safety

These oils are not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet may be referred.

Advice

For any further advice on applications or otherwise please contact the nearest Bharat Petroleum Territory Office or Technical Services Department at the address given below.

Bharat Petroleum Corporation Ltd.

Product and Application Development Dept.
BPCL 'A' Installation, Sewree Fort Road, Sewree (East)
Mumbai -400015
E-mail: MAKcustomercare2@bharatpetroleum.in
Tel No.: 022-24176351