



Search Site

Group Companies: ▾



INDUSTRIAL LUBRICANTS

MAKsimize your success

Home : Lubricants : Automotive Lubricants : Product Details : [Passenger Cars - Petrol Driven – Lubricants](#) : [Automotive Greases](#)

Automotive Greases

[Product Details](#) | [Select your Oil](#) | [Find the distributor](#) | [Promotions](#) | [Enquiry](#)

[MAK UNIVEX CD](#)
[MAK MP GREASE 3](#)
[MAK WB GREASE SPECIAL](#)
[MAK UNIVEX A](#)

MAK MP GREASE 3

NLGI Grade: 2 & 3

Description

This is a premium quality Lithium based multi purpose grease manufactured from superior quality base oil and soap.

Applications

It is recommended for the lubrication of heavy-duty plain and roller bearings operating under heavy loads, high temperature and shock loading conditions.

Performance Benefits

- Excellent structural stability
- Good water resistance property
- Higher drop point
- Very good oxidation stability which ensures longer grease and component life
- Outstanding rust protection ability

Performance Level

IS 7623:1993 Regular type [Reaffirmed 2001]

IPSS : 1-09-006-97

[Agriculture Equipments Lubricants](#)
[Automotive Oils and Greases - Other Applications](#)
[Engine Oil](#)
[Gear Oils](#)
[Greases](#)
[Shock Absorber Fluids](#)
[DG Set / Off Highway Earth moving equipment lubricants](#)
[Passenger / Commercial Vehicles - Diesel Driven – Lubricants](#)
[Passenger Cars - Petrol Driven – Lubricants](#)
[Two/Three Wheel Lubricants](#)

Characteristics	IS 1448	Typical Figures	
		2	3
Consistency of the worked grease at 25°C	P:60		
a)60 double strokes		280	235
b)1,00,000 strokes		25	25
Drop point, °C	P:52	193	194
Free Organic Acidity (as oleic acid), % by mass, max.	P:53	Nil	Nil
Free alkalinety (as LiOH), % by mass	P:53	0.08	0.08
Copper Strip Corrosion Test @ 100 °C for 24 hrs.	P:51	Negative	Negative

Health and Safety

These greases are not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet may be referred.

[Email this page](#) | [Print this page](#) | [Download PDF](#) | [Send an Enquiry](#)

