

MAK SHOCK ABSORBER FLUID DS

This is a tailor made oil blended with superior base oils and fortified with anti-wear, anti-rust and anti-foam additives.

It is approved by **M/s Duroshox** for Shock Absorbers manufactured by them.

- Very good seal compatibility
- Excellent dampening characteristics
- Good anti-foam, anti-wear and anti-rust properties
- Very low pour point which enables its usage over a wider temperature range

- Proprietary brand

Characteristics	ASTM	MAK SHOCK ABSORBER OIL DS
Appearance		Clear & Bright
Colour, Visual Observation	--	Brown
Density @15°C	--	0.8767
K.V at 40° C, cSt	D1298	12.7
Viscosity Index	D445	76
Flash Point, (COC), °C	D2270	180
Pour Point, °C	D92	-39
Aniline point, °C	D611	82
Foaming Tendency / Stability: Qty. of foam in ml a) Sequence I b) Sequence II c) Sequence III	D892	10 / Nil 10 / Nil 10 / Nil

All the mentioned values are typical which may vary from batch to batch.

- Indoor Storage is always preferable.
- Barrels should be kept horizontally with bung position at 3 O'clock 9 O'clock position.
- Barrels should be kept away from dusty or heated areas.
- During handling any contact with dust must be avoided.

This grade is not hazardous under normal conditions of use. For further guidance Material Safety Data Sheet (MSDS) may be referred.

For any further advice on applications or otherwise, please contact the nearest Bharat Petroleum territory office or Technical Services department at the address given below.

Bharat Petroleum Corporation Ltd.

Product and Application Development Dept.
 BPCL 'A' Installation, Sewree Fort Road, Sewree (East)
 Mumbai -400015
 E-mail: MAKcustomercare2@bharatpetroleum.in
 Tel No.: 022-24176351