



## Mobil Super 1000 TM 15W-40

### Premium Multigrade Passenger Vehicle Engine Oil

#### Product Description

The Mobil Super 1000 TM 15W-40 is premium mineral motor oil designed to provide a high level of performance and protection under most operating conditions. Mobil Super 1000 TM 15W-40 is primarily intended for use in Tata Motors Diesel Passenger Vehicles.

#### Features and Benefits

Mobil Super 1000 TM 15W-40 provides very good engine protection and helps extend engine life. In addition, it helps provide:

- Excellent wear protection
- Excellent engine cleanliness

#### Applications

Mobil Super 1000 TM 15W-40 has been developed to meet the latest specifications for engine oils required by Tata Motors. It offers long term engine protection from wear and sludge and deposit build-up. It is recommended by ExxonMobil for use in Tata Motors Passenger Cars and Multi Utility Vehicles where a product approved to their specification SS 6571 is specified.

#### Specifications and Approvals

<b>Mobil Super 1000 TM 15W-40 meets or exceeds the requirements of:</b>	<b>15W-40</b>
API SL	X
API CH-4	X

<b>Mobil Super 1000 TM 15W-40 is recommended by ExxonMobil for use in applications requiring:</b>	<b>15W-40</b>
API CG-4/CF-4	X

<b>Mobil Super 1000 TM 15W-40 has the following builder approvals:</b>	<b>15W-40</b>
Tata Motors Service Fill for Passenger Car Diesels	X
Tata Motors Factory Fill/Service Fill for Multi Utility Vehicles	X

#### Typical Properties

<b>Mobil Super 1000 TM 15W-40</b>	<b>15W-40</b>
SAE Grade	15W-40
Viscosity, ASTM D 445	
cSt @ 40°C	104
cSt @ 100°C	14.4

Viscosity Index, ASTM D 2270	142
Pour Point, °C, ASTM D 97	-33
Flash Point, °C, ASTM D 92	234
Density @ 15 °C, kg/l, ASTM D4052	0.86

## Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet, or will be provided by seller to customers if and as legally required. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, and Mobil Super are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

9-2010

ExxonMobil Lubricants Private Limited  
4th Floor Building 10, Tower C, DLF Cyber City, Gurgaon, Haryana 122002 India

+91 124 6581 601

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com). ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Copyright © 2001-2015 Exxon Mobil Corporation. All rights reserved.