



Mobilfluid 422

Extra High Performance Multipurpose Tractor Fluid

Product Description

Mobilfluid 422 is an extra high performance, multipurpose tractor lubricant engineered to meet or exceed transmission and hydraulic fluid requirements. This product is formulated for the service top-up and refill of transmissions, final drives, and hydraulic systems of farm and industrial tractors and other mobile equipment and especially those with oil-immersed brake systems. This product is designed with special frictional characteristics to prevent squawk and chatter in wet brake systems and to deliver consistent braking performance. Mobilfluid 422 combines high performance base oils and an advanced additive package to deliver the varied lubricant performance properties required by these heavy-duty gear transmissions and heavily loaded final drives.

Features and Benefits

Heavy-duty agricultural and other mobile equipment load, speed, and temperatures have increased the requirements of power transmission fluids to deliver higher performance, increased productivity, and reduced operating costs. Friction control, wear protection, viscosity stability, rust and corrosion protection, and pumpability are features that must be properly balanced to provide extended clutch life, maximum braking efficiency, and reliable operation, even on uneven terrain and over a wide range of ambient temperatures. Mobilfluid 422 delivers outstanding performance in mobile equipment power transmissions, drive axles, clutches, Power Take-Offs (PTO) and hydraulic systems. The key benefits include:

| Features | Advantages and Potential Benefits |
|--|--|
| Enhanced frictional properties especially for immersed disc brakes | Maximum braking efficiency with reduced squawk and brake chatter. Optimised clutch and PTO performance |
| Compatible with clutch materials and elastomers | Longer clutch life, reduced leakage, and reliable response |
| High viscosity index with improved shear stability | All-season performance with consistent hydraulic operation |
| Excellent protection against rust, corrosion, and yellow metal etching | Protects equipment in wet or humid environments and prevents premature wear |
| Excellent low temperature properties | Insures prompt fluid circulation and responsive control under all conditions even in cold weather applications |
| Strong anti-wear and extreme pressure properties | Reduces wear, extends equipment life, and reduces maintenance costs |
| High thermal and oxidation stability | Reduces deposits and sludge to prevent clogged oil ways and impaired hydraulic actuation |
| Good filterability | Keeps systems clean and operating smoothly |

Applications

Recommended by ExxonMobil for use in:

- Heavy-duty transmissions, differentials, final drives, hydraulic systems, power steering systems, wet brakes, PTOs and hydrostatic drives used in agricultural, contractor, and industrial applications
- Top-up and refill of systems
- Sintered bronze oil-immersed disc brakes
- Do not use in passenger car automatic transmissions
- Applications requiring API GL-4 or SAE 80 Grade lubricants in all gear applications except hypoid gear designs

Specifications and Approvals

Mobilfluid 422 meets or exceeds the requirements of the following industry and builder specifications:

Case New Holland ESN-M2C 86-B

Massey Ferguson M-1135

Mobilfluid 422 is recommended by ExxonMobil for use in applications requiring:

| | |
|----------|---|
| API GL-4 | X |
|----------|---|

Typical Properties

Mobilfluid 422

| | |
|------------------------------------|--------|
| SAE Grade | 10W-30 |
| Viscosity, ASTM D 445 | |
| cSt @ 40°C | 85 |
| cSt @ 100°C | 10.8 |
| Brookfield Viscosity, cP (@ -18°C) | 9,000 |
| Viscosity Index, ASTM D 2270 | 110 |
| Pour Point, °C, ASTM D 97 | -30 |
| Flash Point, °C, ASTM D 92 | 226 |
| Density @ 15°C kg/l, ASTM D 4052 | 0.894 |

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, and Mobilfluid are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

1-2011

ExxonMobil Lubricants Private Limited
4th Floor Building 10, Tower C, DLF Cyber City, Gurgaon, Haryana 122002 India

+91 124 6581 601

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Copyright © 2001-2015 Exxon Mobil Corporation. All rights reserved.