

Performance you can trust

## TRI-Logic® VG68 Slideway Lubricant that Extends Cutting Fluid Life

**TRI-Logic® VG68 is a premium quality slideway lubricant designed to be used as part of the ROCOL® TRI-Logic® system. The unique formulation (World patent rights pending) negates the detrimental effects on cutting fluid emulsions usually associated with slideway oils. Rather than acting as a food source for bacteria and fungi, therefore promoting growth, TRI-Logic® VG68 resists degradation and actively reinforces the properties of TRI-Logic® cutting fluids.**

**TRI-Logic® VG68 is formulated to provide excellent lubrication and corrosion protection for machine tool slideway systems. The highly tenacious oil film prevents metal to metal contact, reduces wear and prevents stick-slip.**

**The ROCOL® TRI-Logic® system is a revolutionary approach to maximising cutting fluid sump life, minimising fluid disposal and reducing costs. For optimum performance TRI-Logic® VG68 slideway oil should be used with a TRI-Logic® cutting fluid and, where applicable, TRI-Logic® RTD tapping fluid**

### Features

- Overcomes stick-slip – ensures smooth precise movement.
- High film strength prevents metal to metal contact.
- Reduces wear.
- Extends cutting fluid life.
- Resists degradation.
- Excellent resistance to wash off.
- Protects against corrosion.
- Optimised for use in the TRI-Logic® system.

### Directions for Use

TRI-Logic® VG68 can be used to lubricate slideways on any machine tool where an ISO VG68 lubricant is designated. Ideally lubricator reservoirs should be drained before filling with TRI-Logic® VG68 in accordance with the machine tool manufacturers recommendations.

T +44 (0) 113 232 2600  
F +44 (0) 113 232 2740  
E [customer-service@rocol.com](mailto:customer-service@rocol.com)  
[www.rocol.com](http://www.rocol.com)

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67  
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



BS EN ISO 9001  
Certificate No. FM 12448



BS EN ISO 14001  
Certificate No. EMS 67596



OHSAS 18001  
Certificate No. OHS 78173



INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

# Technical Data

**ROCOL**<sup>®</sup>

Performance you can trust

## TRI-Logic<sup>®</sup> VG68

<b>Appearance</b>	Clear amber liquid
<b>Odour</b>	Mild
<b>Viscosity at 40°C</b>	ISO VG68
<b>Density at 20°C</b>	0.88 g/cm <sup>3</sup>
<b>Storage</b>	Store at normal ambient temperature (5 to 30°C)
<b>Pack Sizes – Part Codes</b>	20 ltr - 52123 60 ltr - 52124 200 ltr - 52129 1000 ltr - 52125

Date: Jan-09

T +44 (0) 113 232 2600  
F +44 (0) 113 232 2740  
E [customer-service@rocol.com](mailto:customer-service@rocol.com)  
[www.rocol.com](http://www.rocol.com)

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67  
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



BS EN ISO 9001  
Certificate No. FM 12448



BS EN ISO 14001  
Certificate No. EMS 67596



OHSAS 18001  
Certificate No. OHS 78173



INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.