

## SERVO LML 2T OIL

### GRADES AVAILABLE – SERVO LML 2T OIL

#### DESCRIPTION

Servo LML 2T Oil is low smoke semi-synthetic two stroke engine oil developed to meet the critical requirements of high performance two stroke engines manufactured by M/s. LML Ltd. It is blended from selected base stocks and additives to minimise spark plug fouling and preignition, prevent rusting, minimise deposit formation and provide protection against seizure, scuffing and wear. It contains a diluent for easy mixing with gasoline.

#### PERFORMANCE BENEFITS

- ☞ Low exhaust smoke
- ☞ Maintains engine cleanliness
- ☞ Minimises spark plug fouling
- ☞ Reduces port deposits and ring sticking
- ☞ Prevents seizure and scuffing
- ☞ Is easily pumpable by oil injection system
- ☞ Ensures reduced oil consumption

#### APPLICATION

Servo LML 2T Oil is recommended for lubrication of two stroke 2 wheelers manufactured by LML Ltd. Kanpur. The recommended dosage is 20 ml of oil per litre of petrol.

#### PERFORMANCE STANDARDS

Meets

- ☞ Latest JASO FC specifications.

#### MANUFACTURERS APPROVAL

- ☞ M/s. LML Ltd. Kanpur has approved LML Servo 2T Oil for two stroke scooters.

### CHARACTERISTICS

	Servo LML 2T Oil
Kinematic Viscosity @ 40°C, cSt	48-70
Flash Point (COC), °C, Min	70
Sulphated Ash, % Wt., Max	0.25

### HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR :

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai – 400 051

**E-Mail:** [tservices@indianoil.co.in](mailto:tservices@indianoil.co.in) OR [tech\\_services@indianoil.co.in](mailto:tech_services@indianoil.co.in)

