



Previous Name: Shell Tactic EMV Albida Grease EP 2

Shell Tactic *EMV Gadus S3 V220C 2*

- Extra Protection
- High Temperature
- Red Lithium Complex

Premium multipurpose extreme-pressure grease

Shell Gadus S3 V220C greases are premium multi-purpose greases based on high viscosity index mineral oil and a lithium complex soap thickener. They contain the latest additives to offer excellent high temperature oxidation performance and other additives to enhance its anti-oxidation, anti-wear and anti-corrosion properties. Shell Gadus S3 V220C greases are especially suitable for bearings operating at high temperature and under load.

DESIGNED TO MEET CHALLENGES

Performance, Features & Benefits

- **Excellent mechanical stability even under vibrating conditions**
Consistency retained over long periods, even in conditions of severe vibration.
- **Enhanced extreme-pressure properties**
Excellent load-carrying performance.
- **Good water resistance**
Ensures lasting protection even in the presence of large amounts of water.
- **High dropping point**
- **Long operational life at high temperatures**
- **Effective corrosion protection**
Effective corrosion protection Ensures components/bearings do not fail due to corrosion.

Main Applications



Shell Gadus S3 V220C greases are used for the grease lubrication of heavy-duty bearings used in machinery found in the following applications:

- Continuous casting
- Vibrating sieves
- Quarries
- Breakers
- Roller conveyors
- Automotive Wheelbearings

Specifications, Approvals & Recommendations

- ASTM D4950-07 LB-GC

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk, or the OEM Approvals website.

Typical Physical Characteristics

Properties			Method	Shell Tactic EMV Gadus S3 V220C 2
NLGI Consistency				2
Colour				Red
Soap Type				Lithium Complex
Base Oil (type)				Mineral
Kinematic Viscosity	@40°C	cSt	IP 71 / ASTM D445	220
Kinematic Viscosity	@100°C	cSt	IP 71 / ASTM D445	19
Cone Penetration Worked	@25°C	0.1mm	IP 50 / ASTM D217	265-295
Dropping Point		°C	IP 396	240
Pumpability Long Distance				Fair

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

- **Health and Safety**

Shell Tactic EMV Gadus S3 V220C 2 is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from <http://www.epc.shell.com/>

- **Protect the Environment**

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Additional Information

- **Re-greasing Intervals**

For bearings operating near their maximum recommended temperatures, re-greasing intervals should be reviewed

- **Advice**

Advice on applications not covered here may be obtained from your Shell representative.