

# ALBAVIS AL 50-600

## DESCRIPTION

ALBAVIS AL 50-600 is a premium industrial machine lubricant satisfying the needs of bearings, gears, slides, guides and certain hydraulic systems. It is formulated with high V.I. paraffinic basestocks, ashless (zinc-free) antiwear protection and is rust and oxidation inhibited. It contains a tackiness agent that increases the adhesiveness of the oil and reduces drip and spatter. ALBAVIS AL 50-600 produces a tough adhesive film on journal and bearing surfaces minimizing oil leakage and waste from plain bearings and protects from shock loading.

## APPLICATION

ALBAVIS AL 50-600 has been specifically designed for "dripless", "non-spatter" applications. Because of its very good anti-wear and tackiness properties, ALBAVIS AL 50-600 is particularly recommended for use in circulatory systems as well as for "once through" applications. ALBAVIS AL 50-600 passes the Bijur Standard Compatibility Test and is approved for use in Bijur lubrication systems.

## BENEFITS

- very good anti-wear properties
- very good adhesiveness
- resistance to hydrolysis and oxidation
- inert towards metals (non-staining and no corrosive wear)
- good filterability characteristics
- rapid water demulsibility
- good low foam/air release characteristics
- approved for use in Bijur lubrication equipment

## TYPICAL DATA

Appearance	clear amber liquid
Density @ 60°F, lbs./gal.	7.30
Color ASTM	3.0
Odor	mild petroleum type
Viscosity @ 40°C, cSt	190
Viscosity Index, minimum	95
Pour Point, °C	-15
Flash Point, COC, °F	255
Tackiness	yes
Copper Strip Corrosion	1a

Issued 9/03 WHC

TOTAL Lubricants USA, Inc.

TOTAL Lubricants USA, Inc. with a policy of continuous improvement, reserves the right to change specifications as our technology progresses.

We are not responsible for the misuse and/or misapplication of our products. ©2002 All rights reserved.

Linden, NJ 07036

5 North Stiles Street  
908.862.9300 800.526.4127

Rockingham, NC 28379

709 Airport Road  
800.323.3198

Knoxville, TN 37914

3315 Riverside Drive  
800.323.3198