

ATL 16A



LUBRICANT



TOTAL

Air Tool Lubricant.

APPLICATIONS

Pneumatic system lubricant.

- **ATL 16A** is a premium product specifically designed to lubricate and prevent corrosion throughout the entire pneumatic system.
- **ATL 16A** contains rust and oxidation inhibitors plus enhanced wear protection for long equipment life.

ADVANTAGES

- Enhanced anti-wear and lubrication properties.
- Rust protection.
- Oxidation stability.
- Longer equipment life.

TYPICAL CHARACTERISTICS	METHODS	ATL 16A
ISO Viscosity Grade		22
Appearance	Visual	Bright and Clear Liquid
Color	ASTM D 1500	< 1.0
Viscosity at 40°C, cSt	ASTM D 445	18.9 - 24.2
Viscosity at 100°C, cSt	ASTM D 445	4.0
Viscosity Index	ASTM D 2270	92
Pour Point, °F	ASTM D 97	-4
Flash Point, COC, °F	ASTM D 92	388 min.
Density @ 60°F, lbs./gal.	ASTM D 1298	7.18

TOTAL Lubricants USA, Inc.

Linden, NJ 07036
5 North Stiles Street
908.862.9300/800.526.4127

Rockingham, NC 28379
709 Airport Road
800.323.3198 / 800.526.4127

Knoxville, TN 37914
3315 Riverside Drive
800.323.3198 / 800.526.4127