


BRICK GREASE L



GREASE



TOTAL

Lithium Based Brick Grease.

APPLICATIONS

- **BRICK GREASE L** is a premium quality, lithium based brick grease used in open well top fed mills. It has a high melting point which prevents drip spoilage of goods in process.
- **BRICK GREASE L** eliminates the danger of dry bearings and reduces lubrication costs. It applies a perfect film of grease to the shaft.
- Note: Cut pieces of brick small enough to allow free movement and prevent "bridging" or jamming.
- Applications include: Ball & Pebble mills (Abbe, Marcy, Patterson, & other types), calendar rollers (laundry), crushers (water jacketed), rolling mill bearings (metal), and rubber mill (drive shaft bearings).
- **BRICK GREASE L** is packaged 12 bricks to a case (17.5" X 12.0" X 9.0"). Each case weights 50 pounds. The dimensions of each brick is 3.5" X 4.5" X 9.0".

ADVANTAGES

- High melting point.
- Lasts longer.
- Excellent lubricity properties.
- Eliminates danger of dry bearings.
- Reduces lubrication costs.
- Applies perfect film to shaft.
- Good heat resistance.

TYPICAL CHARACTERISTICS	METHODS	BRICK GREASE L
Appearance	Visual	Light Amber to Dark Brown
Application Range, °F		0-275
Intermittent Range, °F		325
Base Oil Viscosity @ 40°C, cSt	ASTM D 445	450-550
Dropping Point, °F, min.	ASTM D 2265	340
Penetration, Unworked		45-65
Soap Base Type		Lithium

TOTAL Lubricants USA, Inc.

Linden, NJ 07036
5 North Stiles Street
908.862.9300/800.526.4127

Rockingham, NC 28379
709 Airport Road
800.323.3198 / 800.526.4127

Knoxville, TN 37914
3315 Riverside Drive
800.323.3198 / 800.526.4127