

DYNATRANS LM

SAE 10W-30



Lawn mower transmission Fluid

APPLICATIONS

All types of service

- **DYNATRANS LM** is designed to meet lubrication requirements of lawn mower transmissions..
- **DYNATRANS LM** is formulated to provide excellent oxidation stability and low temperature flow properties.
- Recommended for certain mobile equipment transmissions

PERFORMANCE

Tuff Torque lawn mower transmissions.

CUSTOMER BENEFITS

High technical performance

- **DYNATRANS LM** contains enhanced detergents, dispersants, anti-oxidants, anti-wear and corrosion prevention properties improve the fluid performance under all types of service.
- This fluid contains friction modifiers to lower friction.
- Enhanced performance under all seasons due to high viscosity index.

CHARACTERISTICS

TYPICAL PROPERTIES—DYNATRANS LM 10W-30	
SAE grade	10W-30
Density at 60 F ASTM D 1298	0.867
Viscosity, cSt @ 100°C ASTM D 445	10.5
Viscosity, cSt @ 40°C ASTM D 445	62
Cold Crank cp max ASTM D 5293	6100@-25 C
Viscosity Index ASTM D 2270	150+
Pour Point, °C ASTM D 97	-30
Total base number ASTM D 2896	

TOTAL Lubricants USA, Inc.

Dynatrans LM Oils

Sheet updated: 9/4/2013

5 North Stiles Street
Linden, New Jersey 07036
908.862.9300 or 800.323.3198
www.totallubricants.com

TOTAL Lubricants USA has a policy of continuous improvement and reserves the right to change specifications as our technology progresses.
We are not responsible for the misuse and/or misapplication of our products. MSDS are found on our web sites.