


# HDLL COOLANT 50-50



ANTIFREEZE &  
HEAT TRANSFER



**TOTAL**

Red heavy-duty long life ready-to-use coolant

## APPLICATIONS

HD Diesel coolant with  
extremely long life

- **HDLL COOLANT** is a high performance, long-life ethylene glycol coolant suitable for heavy duty diesel and natural gas engines.
- **HDLL (Heavy Duty Long Life) COOLANT** contains organic acid technology and heavy duty corrosion inhibitors (nitrites and molybdates) to provide long life protection of cooling systems parts.
- **HDLL COOLANT** is free from nitrate, borate, phosphate, silicate and amine.
- This is a ready-to-use coolant.

## SPECIFICATIONS

International standards

- ASTM D-3306 (Automotive service), D-6210 (HD Diesel)
- ASTM D 5345 (prediluted HD Diesel); SAE J 1034
- Truck Maintenance Council RP-329, RP-338

OEM standards

- Caterpillar EC-1; Chrysler MS 9769; Cummins 90T8-4
- Detroit Diesel 7SE-298;
- General Motors 1899-M and 1825-M
- John Deere H24A1, H24C1
- Mack Truck; Navistar B 1
- Mercedes DBL 7700
- Volvo/GM Heavy Truck

## ADVANTAGES

High technical  
performance

Long service life

- Superior corrosion protection
- High boiling point and low freezing point
- Easy to identify heavy duty red color
- At 300,000 miles addition of extender allows 600,000 mile protection
- Contains a bitter tasting additive as a deterrent for pets and children

### TYPICAL CHARACTERISTICS—HDLL COOLANT 50-50

Color, visual	Red	Freeze Point, °F (°C)	-34 (-37)
Specific Gravity @ 60/60 °F	1.06	Flash point, °F (°C) (ASTM D 92)	250 (121)
Density, lbs/gal	8.84	Reserve alkalinity, ml (ASTM D 1121)	2.9
Composition, wt %		Foam Resistance (ASTM D-1881)	
Total glycols, wt%, min. (ASTM E 202)	47.5	Foam Volume, 150 ml max.	50
Total water, wt% max. (ASTM D 1123)	49	Foam Break, 5 seconds max.	5
Chlorides, 25 ppm max	10	Ash, wt%, 2.5% max	1.0

**TOTAL Lubricants USA, Inc.**

**HDLL Coolant 50-50**

Sheet updated: 5/1/2013

5 North Stiles Street  
Linden, NJ 07036  
908.862.9300 or 800.323.3198  
[www.totallubricantsusa.com](http://www.totallubricantsusa.com)