Lical WR EP





Lithium-Calcium Soap, Water Resistant Steel Mill Grease.

APPLICATIONS

Extreme Pressure, extremely water resistant grease.

- Lical WR EP grease is extremely water resistant grease formulated to provide outstanding lubrication properties in very wet environments such as those found in steel mill operations.
- Lical WR EP grease is primarily recommended for heavily loaded journal, plain and anti-friction bearings subjected to water.

ADVANTAGES

- Extremely water resistant.
- · Incorporates anti-corrosion additives.
- Seals against dirt and water.
- · Readily pumpable in cold conditions.

TYPICAL CHARACTERISTICS	METHODS	Lical WR EP 2
		TYPICAL DATA
Appearance	Visual	Dark Green
Operating Range, °F		0 - 250
Thickener Type		Lithium-Calcium
NLGI Grade	ASTM D 217	2
Penetration Worked, 60xx	ASTM D 217	260 - 280
Dropping Point, °F	ASTM D 2265	393
Corrosion Prevention	ASTM D 1743	Pass
Four Ball Weld Load, kg	ASTM D 2783	315
Wet Roll Stability, 10%water	ASTM D 1831	2.7
Water Washout, %wt. loss @ 175F	ASTM D 1264	1.3
Water Spray Off, %wt.	ASTM D 4049	3.2
Base oil viscosity @ 40 C	ASTM D 445	478
Timken OK load	ASTM D2509	60

Revised 9-25-2012 by AD

TOTAL Lubricants USA, Inc.

Linden, NJ 07036 5 North Stiles Street 908.862.9300/800.526.4127

Rockingham, NC 28379709 Airport Road
800.323.3198 / 800.526.4127