

MINERAL SEAL OIL 600



LUBRICATION



Process oil applications

APPLICATIONS

High quality
low-viscosity oil

- **MINERAL SEAL OIL 600** is a low viscosity process oil made from high quality base oil refining. It is often used as a processing oil or compounding stock (shoe polish, etc) or a solvent rather than a lubricant. It may also be used as a fuel for pot burners in orchards.
- **MINERAL SEAL OIL 600** may also be used as seal oil, scrubbing/adsorption oil, or a cold rolling oil for metal . It contains no antifoam or additives.

ADVANTAGES

- Perfectly suitable for blending
- Bright and clear with very low color
- Good lubricity
- Non-staining

TYPICAL CHARACTERISTICS—SEAL OIL 600 OIL

Viscosity at 40°C, cSt (ASTM D 445)	3.4
SUS at 100°F (ASTM D 2161)	38
Color (ASTM D 1500)	L0.5
Density @ 60 °F, lbs. /gal. (ASTM D 1298)	7.3
Specific Gravity @ 60/60°F (ASTM D 1298)	0.881
Flash point, COC, °F (°C) (ASTM D 92)	227 (108)
Pour point, °F (°C) (ASTM D 97)	-80 (-62)
Copper strip corrosion (ASTM D 130)	1A
Aniline point °F (°C) (ASTM D 611)	142 (61)
Aromatic content, vol.% (ASTM D 2007)	37

TOTAL Lubricants USA

TOTAL Lubricants USA, Inc.

400 Chisholm Place, Suite 418
Plano, Texas 75075
800-442-5823 or 469-241-0950
www.finalube.com

Mineral Seal Oil 600
Sheet updated: 11/2009
AD

5 North Stiles Street
Linden, New Jersey 07036
800-526-4127 or 908-862-9300
www.total-us.com

TOTAL Lubricants USA has a policy of continuous improvement and reserves the right to change specifications as our technology progresses.
We are not responsible for the misuse and/or misapplication of our products. MSDS are found on our web sites.