

MOLDOL 512 S



DEMOLDING



TOTAL

Concrete Mold Release Oil.

APPLICATIONS

- **MOLDOL 512 S** is a specialized lubricant designed for all types of forms including steel, wood, and high density overlay. It contains a unique combination of light petroleum oils compounded with wetting agents to promote a thorough and uniform coating on form surfaces. Special additives protect against rust and corrosion and make this product safe for ferrous and non-ferrous type forms.
- **MOLDOL 512 S** is generally applied through automatic spray systems in order to assure a consistent film. However, manual spraying, swabbing, rolling, or brush application is acceptable.

ADVANTAGES

- Ensures good lubricant film.
- Promotes good surface finish.
- Mild odor.
- Excellent wetting ability.
- Non-staining.
- Minimal amount of residue left of molds.

TYPICAL CHARACTERISTICS	METHODS	MOLDOL 512 S
Appearance	Visual	Clear Amber Liquid
Color	ASTM D 1500	2.5
Viscosity at 40°C, cSt	ASTM D 445	12.0
Density @ 60 °F, lbs./gal.	ASTM D 1298	7.26
Specific Gravity @ 60/60 °F	ASTM D 1298	0.871
Flash Point, COC, °F	ASTM D 92	350
Fire Point, COC, °F	ASTM D 92	365

TOTAL Lubricants USA, Inc.

Linden, NJ 07036

5 North Stiles Street
908.862.9300/800.526.4127

Rockingham, NC 28379

709 Airport Road
800.323.3198 / 800.526.4127

Knoxville, TN 37914

3315 Riverside Drive
800.323.3198 / 800.526.4127