

NATERIA CATCO SYN. NA



SAE 40

NATURAL GAS
ENGINE OIL



Synthetic low-ash natural gas engine oils

APPLICATIONS

All types of severe service
and extended drain service

- Lubrication of gas engines used in cogeneration or standard power plants where the manufacturer requires an ash level of 0.4 to 0.5 weight percent.
- Highly recommended for engines working under severe operating conditions such that conventional mineral oils cannot be used.
- Highly recommended for applications requiring very long drain intervals.

ADVANTAGES

Less downtime
Lower maintenance costs
Better plant efficiency

Technical characteristics

- Compared to the low ash mineral based lubricants, **NATERIA CATCO SYNTHETIC NA** allows a very important increase of the drain intervals. Thus it generates a lowering of the cost and less engine stop for maintenance.)
- The use of **NATERIA CATCO SYNTHETIC NA** in real situation decreases dramatically the oil consumption. Consequently there is a very low deposit amount on the heat exchangers tubes. This favors cogeneration installation efficiency.
- Oil consumption reduction and easier starts in cold weather
- Engine thermal efficiency improvements and horsepower improvements in BHP-hr lead to fuel economy improvements.
- Exceptional detergency and dispersancy.
- High chemical stability with excellent resistance to oxidation and nitration.
- Excellent anti-wear, anti-corrosion and anti-foam resistance.

TYPICAL CHARACTERISTICS--NATERIA CATCO SYNTHETIC NA	
SAE grade	40
Specific gravity @ 60/60°F (ASTM D 1298)	0.
Viscosity @ 40°C, cSt (ASTM D 445)	100
Viscosity @ 100°C, cSt (ASTM D 445)	14.6
Viscosity index (ASTM D 2272)	155
Pour point, °F (°C) (ASTM D 97)	-30 (-34)
Flash point °F (°C) (ASTM D 92)	490 (254)
TBN (ASTM D 2896)	5.25
Sulfated ash, wt% (ASTM D 874)	0.49

TOTAL Lubricants USA, Inc.

400 Chisholm Place, Suite 418,
Plano, Texas 75075
800-442-5823 or 469-241-0950
www.total-us.com

Nateria Catco Synthetic NA
Sheet updated: 5/10/2010

5 North Stiles Street
Linden, NJ 07036
908.862.9300 or 800.526.4127
www.total-us.com

TOTAL Lubricants USA with a policy of continuous improvement, reserves the right to change specifications as our technology progresses.
We are not responsible for the misuse and/or misapplication of our products. MSDS are found on our web sites.