NEPTUNA 2T SUPER SPORT







Water cooled 2-cycle outboard engine oil

APPLICATIONS 2-stroke engines NEPTUNA 2T SUPER SPORT is specially formulated for pleasure craft engines that are water cooled. Mixing of the oil with the fuel should be in accordance with the manufacturer's recommendations. It is suitable for air-cooled engines calling for JASO FB quality level. PERFORMANCE NMMA TC-W3 officially approved. RL-13020P Other claims, OEMs Meets air cooled requirements of API TC and JASO FB. Conforming to the manufacturer's recommendations including: Johnson, Mariner, Mercury, Suzuki, Yamaha... CUSTOMER BENEFITS

High technical performance	• Fortified detergent capability prevents clogging of ports, ring sticking and spark plug fouling
	 Increased lubrication capacity which prevents seizure
	 Anti-rust and anti-corrosion properties protect engines during prolonged periods of layup.

CHARACTERISTICS

TYPICAL CHARACTERISTICS—NEPTUNA 2T SUPER SPORT		
Density at 15°C, (ASTM D 1298)	0.863	
Viscosity, cSt @ 100°C (ASTM D 445)	8.2	
Viscosity, cSt @ 40°C (ASTM D 445)	54.5	
Color, visual	Blue	
Flash point °C (°F) ASTM D 92	138 (280)	
Pour point °C (°F) ASTM D 97	-36 (-33)	
Sulfated ash	Nil	
NMMA certification number	RL-00288J	

TOTAL Lubricants USA, Inc.

Neptuna 2T Super Sport Sheet updated: 8/28/2014 5 North Stiles Street Linden, New Jersey 07036 800-323-3198 or 908-862-9300 www.totallubricantsusa.com.

TOTAL Lubricants USA has a policy of continuous improvement and reserves the right to change specifications as our technology progresses. We are not responsible for the misuse and/or misapplication of our products. MSDS are found on total-techspecs.com