

PENKOTE



LUBRICATION



TOTAL

Penetrating Lubricant and Rust Preventative.

APPLICATIONS

- **PENKOTE** is a versatile, highly penetrating rust preventative that protects your tools and work-in-progress against rust and corrosion. The low viscosity of this lubricant assures that crevices and pores are effectively penetrated to provide complete surface coverage. **PENKOTE** displaces moisture and ensures that a thin, non-gumming film is left to serve as a protective barrier. Protection can last up to 12 months for indoor applications.
- **PENKOTE** resists oxidation and is non-staining. It can be safely applied to all metals and surfaces. **PENKOTE** not only protects against rust, it cleans and speeds disassembly of rusted and corroded parts. The good dielectric properties assist in preventing electrical shorts when starting wet motors.
- Uses include: work-in-progress, idle or stored machine tools, finished parts or molds, tools, dies, fixtures, jigs, bearings, gauges, instruments, chains, moving parts, cams, slides, rusted nuts and bolts, and corroded parts.

ADVANTAGES

- Displaces moisture.
- Penetrates quickly.
- Excellent rust buster.
- Pleasant odor.
- Safe for all metal surfaces.
- Low surface tension.
- Provides long term rust protection.

TYPICAL CHARACTERISTICS	METHODS	PENKOTE
Appearance	Visual	Clear Light Yellow Liquid
Viscosity at 100°F, SUS	ASTM D 445	32
Flash Point, COC, °F	ASTM D 92	100 min.
Density @ 60°F, lbs./gal.	ASTM D 1298	6.86
Specific Gravity @ 60°/60°F	ASTM D 1298	0.822
Setting Time, hrs.		3.0
Film Thickness, mils.		0.40
Coverage, ft ² /gal.		800
Humidity Cabinet, days	ASTM D 1748	60
Salt Spray, hrs.	FED STD	60+
4 Ball Wear Test, mm	ASTM D 4172	26.4
Water Displacement	MIL-C-16173D	Pass

TOTAL Lubricants USA, Inc.

Linden, NJ 07036
5 North Stiles Street
908.862.9300/800.526.4127

Rockingham, NC 28379
709 Airport Road
800.323.3198 / 800.526.4127

Knoxville, TN 37914
3315 Riverside Drive
800.323.3198 / 800.526.4127