

PURE GEAR OIL



NON-CRITICAL
LUBRICATION



API GL-1 (non-additized) gear oil

APPLICATIONS

- **PURE GEAR OILS** are economical lubricant containing no additives.
- **PURE GEAR OILS** satisfy API Service GL-1 specifications. They are primarily used in truck manual transmissions. In some cases they may be recommended for automotive worm gears or as dedusting oils.

ADVANTAGES

- Good lubricity and low odor
- Good low temperature flow properties
- Low odor

TYPICAL CHARACTERISTICS—PURE GEAR OIL		
SAE grade	90	140
Specific gravity @ 60/60 °F (ASTM D 1298)	0.887	0.891
Viscosity at 40°C, cSt (ASTM D 445)	226	480
Viscosity at 100°C, cSt (ASTM D 445)	19	32
Viscosity index (D 2272)	94	97
Pour point, COC, °F (°C) (ASTM D 97)	0 (-18)	5 (-15)
Color, (ASTM D 1500)	6.0	6.5

TOTAL Lubricants USA, Inc.

Pure Gear Oil
Sheet updated: 7/23/2013
(Former Pure Mineral Gear Oil)

5 North Stiles Street
Linden, New Jersey 07036
908.862.9300 or 800.323.3198.
www.totallubricantsusa.com

TOTAL Lubricants USA has a policy of continuous improvement and reserves the right to change specifications as our technology progresses.
We are not responsible for the misuse and/or misapplication of our products. MSDS are found on our web sites.