SCILIA 32 S





Chlorine-free Cutting Oil for Severe Machining and Machine Tool Lubrication.

APPLICATIONS

- SCILIA 32 S is a low odor, non-staining, neat cutting oil dedicated to both ferrous and non-ferrous metals and to the lubrication of various machine parts: bearings, gears, and slideways.
- SCILIA 32 S is widely used on cutting operations such as screw cutting on copper alloys, aluminum, low carbon steels, medium, hard, and stainless steels, bronze, tin, nickel, high nickel steel, and heat resistant alloys. It is recommended for all general machining operations, heavy load and high speed operations, and on difficult to machine alloys.
- SCILIA 32 S can be utilized as a dual purpose oil in low pressure lube systems
 where cross contamination of cutting oil and lube oil is a problem.

ADVANTAGES

- Excellent anti-wear and extreme pressure performance.
- Promotes excellent surface finish.
- Excellent lubricity properties--Increases the tool life on a large scale of cutting parameters maintaining an additive layer on the chip / workpiece / tool surface.
- Excellent metal wetting ability.
- Non-staining.
- Very good oxidation resistance.
- Excellent compatibility with seals and paints.

TYPICAL CHARACTERISTICS	SCILIA 32 S
TITIOAL CHARACTERISTICS	
Appearance	Clear Yellow Liquid
Color, ASTM D-1500	1.0
Viscosity at 40°C, cSt	28.8 - 35.2
Density @ 60 °F, lbs./gal.	7.27
Specific Gravity @ 60/60 °F	0.872
Flash Point, COC, °F	380
Copper Strip Corrosion	1A-1B
Lubricity Content, %wt.	5.0
Sulfur Content, %wt.	1.0
Chlorine Content, %wt.	Nil

TOTAL Lubricants USA, Inc

Linden, NJ 07036 5 North Stiles Street 908.862.9300/800.526.4127 Rockingham, NC 28379 709 Airport Road 800.323.3198 / 800.526.4127 Knoxville, TN 37914 3315 Riverside Drive 800.323.3198 / 800.526.4127