

DESCRIPTION

Marine oil resulting from the latest innovation in additive component technology. Especially designed for the cylinder lubrication of slow speed 2-stroke diesel engines when running with low sulfur fuel.

APPLICATIONS

Allowing for the most stringent conditions encountered in service, **TALUSIA LS 40** covers the special operational needs when using so called low sulfur fuel.

PROPERTIES

This lubricant assures:

- minimal piston ring and liner wear.
- maximum cleanliness.
- reduced engine maintenance costs.
- extended periods between overhauls.

APPROVALS

TALUSIA LS 40 satisfies the requirements and recommendations of the major engine manufacturers.

CHARACTERISTICS

CHARACTERISTICS	METHODS	UNITS	TALUSIA LS 40
S.A.E. Grade			50
Density at 15 °C	ISO 3675	kg/m ³	920
Kinematic viscosity at 100 °C	ISO 3104	mm ² /s	20
Flash Point (COC)	ASTM D 92	°C	> 230
Pour Point	ISO 3016	°C	- 9
BN	ASTM D 2896	mgKOH/g	40

Characteristics of this chart are indicative typical values

HANDLING, HEALTH AND SAFETY

TALUSIA LS 40 consists of highly refined mineral oils with specific additives.

In normal conditions of use, these lubricants present no particular toxic hazard.

All lubricants, of any kind, should always be handled with great care, particularly avoiding any contact with the skin.

Prevent any risk of splashing, and keep away from combustible materials.

Store under cover and away from any risk of contamination.

A safety data sheet complying with current legislation is available on [www. quickfds.com](http://www.quickfds.com) or www.lubmarine.com.

The values shown above are typical values at the date of publication. TOTAL Lubmarine reserves the right to change these typical values without prior notice.



TOTAL LUBRIFIANTS
562 avenue du Parc de l'Île – 92029 Nanterre Cedex
Tel.: 33.1.41.35.59.23 – Fax: 33.1.41.35.20.92
www.lubmarine.com - rm.tma-diagomarplus@total.com

LUBMARINE 15/4GB - 1006